

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 081 692 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
07.03.2001 Bulletin 2001/10

(51) Int. Cl.⁷: **G11B 7/135**

(21) Application number: **00118627.9**

(22) Date of filing: **28.08.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **01.09.1999 JP 24729499**
06.03.2000 JP 2000060843

(71) Applicant: **KONICA CORPORATION**
Tokyo (JP)

(72) Inventors:
• **Ota, Kohei,**
c/o Konica Corporation
Hachioji-shi, Tokyo (JP)
• **Kimura, Tohru,**
c/o Konica Corporation
Hachioji-shi, Tokyo (JP)

(74) Representative:
Henkel, Feiler, Hänzeler
Möhlstrasse 37
81675 München (DE)

(54) **Objective lens for pickup and light pickup apparatus**

(57) An objective lens for use in an optical pickup apparatus to record or reproduce information in an optical information recording medium, comprises an aspheric surface, wherein the following conditional formula is satisfied: $1.1 \leq d1/f \leq 3$ where $d1$ represents axial lens thickness and f represents a focal length.

FIG. 1 (a)





FIG. 1 (b)



Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to an objective lens for pickup in an optical recording apparatus which conducts recording on or reproducing from an information recording medium such as an optical disk, and to a optical pickup apparatus employing the objective lens.

[0002] In an optical system of an optical recording/reproducing apparatus employing a medium of an optical disk, there is commonly used an aspherical single objective lens. For achieving high density of recorded information signals, a size of a spot formed on a recording medium by the objective lens has been required to be small, and there have been investigated high NA of an objective lens and utilization of a light source for short wavelength.

[0003] Though there has been developed a GaN blue semiconductor laser having an oscillation wavelength of about 400 nm, a wavelength is varied by mode hop or by laser output, and monochromaticity of oscillation wavelength is poor because high-frequency superimposition is used. Therefore, in a light-converging optical system for high density optical disk wherein a GaN blue semiconductor laser is used, it is considered that correction of axial chromatic aberration is necessary.

[0004] In an aspherical single objective lens for an optical disk, spherical aberration and coma are corrected by aspherical surfaces. However, when a numerical aperture is large, image height characteristics are deteriorated. When an optical disk is made to be of higher density, deterioration of the image height characteristics becomes an extremely serious problem even if the value of the deterioration is small. In particular, when the numerical aperture is 0.65 or more, the problem is conspicuous. Further, when the numerical aperture is greater, deterioration of eccentricity sensitivity is also a serious problem.

SUMMARY OF THE INVENTION

[0005] The invention has been achieved for solving the problem stated above. Namely, with regard to an objective lens for a optical pickup apparatus, an object of the invention is to provide an aspherical single objective lens whose numerical aperture is great and image height characteristics are excellent. In particular, an object of the invention is to provide an objective lens which is suitable to be used for a high density recording/reproducing apparatus wherein a numerical aperture is not less than 0.65, preferably 0.7 or more, and more preferably 0.75 or more, and there is used a laser wherein a wavelength of a light source is as short as about 500 nm.

[0006] Further, providing an objective lens which makes eccentricity sensitivity to be excellent is also an object of the invention. Furthermore, providing an objective lens which makes spherical aberration and coma to be excellent is also an object of the invention.

[0007] When a thickness of a protective layer (transparent base board) of an information recording medium is small to be 0.2 mm or less, or when there is no protective layer, a working distance can be small. An offer of an objective lens which is suitable to be used in a recording/reproducing apparatus having such small working distance is an object of the invention.

[0008] It is further an object of the invention to provide a optical pickup apparatus, an optical information recording medium recording/reproducing apparatus, and an optical information recording medium recording/reproducing method, which employ these objective lenses stated above.

[0009] Further, an object is to provide a optical pickup apparatus having an optical system wherein axial chromatic aberration is corrected by the simple structure, in a high density optical recording/reproducing apparatus. In particular, it is an object to provide a optical pickup apparatus wherein a numerical aperture on the part of an information recording medium is 0.65 or more, preferably 0.7 or more, and more preferably 0.75 or more, and shortest wavelength of a light source to be used is as small as 500 nm or less.

[0010] The above object can be attained by the following structures.

(1) An objective lens for use in an optical pickup apparatus to record or reproduce information in an optical information recording medium, comprising:

an aspheric surface;
wherein the following conditional formula is satisfied:

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness and f represents a focal length.

EP 1 081 692 A2

(2) In the objective lens of (1), a numerical aperture of the objective lens is not smaller than 0.65.

(3) In the objective lens of (2), a numerical aperture of the objective lens is not smaller than 0.75.

(4) In the objective lens of (1), the following conditional formula is satisfied:

5
$$f/vd \leq 0.060$$

where v d represents Abbe's number.

(5) In the objective lens of (1), the following conditional formula is satisfied:

10
$$1.40 \leq n$$

where n represents a refractive index at a used wavelength.

(6) In the objective lens of (5), the following conditional formula is satisfied:

15
$$1.40 \leq n \leq 1.85$$

(7) In the objective lens of (1), the following conditional formula is satisfied:

20
$$0.40 \leq r1/(n \cdot f) \leq 0.70$$

where r1 represents a paraxial radius of curvature of one surface of the objective lens.

(8) In the objective lens of (7), r1 represents a paraxial radius of curvature of the surface of the objective lens at the light source side.

(9) In the objective lens of (1), a used wavelength is not longer than 500 nm.

25 (10) In the objective lens of (1), the objective lens is an objective lens for use in an optical pickup apparatus to record or reproduce information in an optical information recording medium having a protective layer whose thickness is not larger than 0.2 mm.

(11) In the objective lens of (10), a numerical aperture is not smaller than 0.7.

(12) In the objective lens of (7), the following conditional formula is satisfied:

30
$$1.50 \leq n$$

where n represents a refractive index at a used wavelength.

(13) In the objective lens of (1), the objective lens is a plastic lens.

35 (14) In the objective lens of (1), the objective lens is a glass lens.

(15) In the objective lens of (1), the following conditional formula is satisfied:

$$1.85 \leq n$$

40 where n represents a refractive index at a used wavelength.

(16) In the objective lens of (1), the objective lens further comprises a diffracting section.

(17) In the objective lens of (1), the objective lens further comprises a flange section on an outer periphery thereof.

(18) In the objective lens of (1), the flange section comprises a surface extended in a direction perpendicular to an optical axis.

45 (19) In the objective lens of (1), each of both lens surfaces is an aspherical surface.

(20) An optical pickup apparatus to record or reproduce information in an optical information recording medium, comprises:

a light source to emit light flux;

50 a converging optical system to condense the light flux emitted from the light source; and

an optical detector to detect reflection light from the optical information recording medium; wherein the converging optical system comprises an objective lens to condense the light flux on an information recording surface of the optical information recording medium and the objective lens comprises an aspheric surface; and wherein the following conditional formula is satisfied:

55
$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective

EP 1 081 692 A2

lens.

(21) In the optical pickup apparatus of (20), a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.65.

(22) In the optical pickup apparatus of (29), a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.75.

(23) In the optical pickup apparatus of (20), the following conditional formula is satisfied:

$$f/vd \leq 0.060$$

where v d represents Abbe's number of the material of the objective lens.

(24) In the optical pickup apparatus of (20), the following conditional formula is satisfied:

$$1.40 \leq n$$

where n represents a refractive index of the material of the objective lens at a used wavelength.

(25) In the optical pickup apparatus of (24), the following conditional formula is satisfied:

$$1.40 \leq n \leq 1.85$$

(26) In the optical pickup apparatus of (20), the following conditional formula is satisfied:

$$0.40 \leq r1/(n \cdot f) \leq 0.70$$

where $r1$ represents a paraxial radius of curvature of the surface of the objective lens at the light source side.

(27) In the optical pickup apparatus of (20), the light source emits light flux whose wavelength is not larger than 500 nm.

(28) In the optical pickup apparatus of (20), the optical pickup apparatus is used to record or reproduce information in an optical information recording medium having a protective layer whose thickness is not larger than 0.2 mm.

(29) In the optical pickup apparatus of (28), a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.7.

(30) In the optical pickup apparatus of (20), the following conditional formula is satisfied:

$$1.85 \leq n$$

where n represents a refractive index of a material of the objective lens at a wavelength of the light flux emitted from the light source.

(31) In the optical pickup apparatus of (20), the converging optical system comprises a diffracting section.

(32) In the optical pickup apparatus of (20), the converging optical system comprises a coupling lens to change a divergent angle of the light flux emitted from the light source and the coupling lens corrects chromatic aberration of the objective lens.

(33) In the optical pickup apparatus of (32), the coupling lens is a collimator lens to make the light flux emitted from the light source to be parallel light flux.

(34) In the optical pickup apparatus of (32), chromatic aberration of the composite system of the objective lens and the coupling lens satisfies the following conditional formula:

$$\delta fb \cdot NA^2 \leq 0.25 \mu m (\delta fb > 0)$$

where δfb represents a change of focal position (μm) of the composite system when a wavelength is changed from a standard wavelength by +1 nm, and NA represents a numerical aperture of the objective lens at the optical information recording medium side.

(35) In the optical pickup apparatus of (34), the chromatic aberration of the composite system of the objective lens and the coupling lens satisfies the following conditional formula:

$$0.02 \mu m \leq \delta fb \cdot NA^2 \leq 0.15 \mu m (\delta fb > 0)$$

(36) In the optical pickup apparatus of (32), the following conditional formula is satisfied:

$$0.1 \leq |m| \leq 0.5 \quad (m < 0)$$

where m represents magnification of the composite system of the objective lens and the coupling lens.

(37) In the optical pickup apparatus of (32), the coupling lens is a single lens group having two lenses.

(38) In the optical pickup apparatus of (32), the coupling lens comprises an aspherical surface.

(39) In the optical pickup apparatus of (32), the coupling lens comprises a diffracting section.

(40) An apparatus to record or reproduce information in an optical information recording medium, comprises:

an optical pickup apparatus, comprising

a light source to emit light flux;

a converging optical system to condense the light flux emitted from the light source; and

an optical detector to detect reflection light or transmission light from the optical information recording medium;

wherein the converging optical system comprises an objective lens to condense the light flux on an information recording surface of the optical information recording medium and the objective lens comprises an aspheric surface; and wherein the following conditional formula is satisfied:

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective lens.

(41) A method of recording or reproducing information in an optical information recording medium, comprises:

a step of emitting light flux;

a step of converging the light flux emitted from the light source on an information recording surface of the optical information recording medium; and

a step of detecting reflection light or transmission light of the light condensed on the information recording surface;

wherein the light flux is converged on the information recording surface of the optical information recording medium by an objective lens; and

wherein the objective lens comprises an aspheric surface and the following conditional formula is satisfied:

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective lens.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011]

Fig. 1(a) shows a sectional view of an objective lens and Fig. 1(b) shows aberration diagrams of the objective lens in Example 1.

Fig. 2(a) shows a sectional view of an objective lens and Fig. 2(b) shows aberration diagrams of the objective lens in Example 2.

Fig. 3(a) shows a sectional view of an objective lens and Fig. 3(b) shows aberration diagrams of the objective lens in Example 3.

Fig. 4(a) shows a sectional view of an objective lens and Fig. 4(b) shows aberration diagrams of the objective lens in Example 4.

Fig. 5(a) shows a sectional view of an objective lens and Fig. 5(b) shows aberration diagrams of the objective lens in Example 5.

Fig. 6(a) shows a sectional view of an objective lens and Fig. 6(b) shows aberration diagrams of the objective lens in Example 6.

Fig. 7(a) shows a sectional view of an objective lens and Fig. 7(b) shows aberration diagrams of the objective lens in Example 7.

Fig. 8 is a diagram showing an embodiment of a optical pickup apparatus employing an objective lens of the inven-

tion.

Fig. 9 shows a sectional view of an objective lens in Example 8.

Fig. 10 shows aberration diagrams of the objective lens in Example 8.

Fig. 11 shows a sectional view of an objective lens in Example 9.

5 Fig. 12 shows aberration diagrams of the objective lens in Example 9.

Fig. 13 shows a sectional view of an objective lens in Example 10.

Fig. 14 shows aberration diagrams of the objective lens in Example 10.

Fig. 15 shows a sectional view of an objective lens in Example 11.

Fig. 16 shows aberration diagrams of the objective lens in Example 11.

10 Fig. 17 shows a sectional view of an objective lens in Example 12.

Fig. 18 shows aberration diagrams of the objective lens in Example 12.

Fig. 19 shows a sectional view of an objective lens in Example 13.

Fig. 20 shows aberration diagrams of the objective lens in Example 13.

Fig. 21 shows a sectional view of an objective lens in Example 14.

15 Fig. 22 shows aberration diagrams of the objective lens in Example 14.

Fig. 23 shows a sectional view of an objective lens in Example 15.

Fig. 24 shows aberration diagrams of the objective lens in Example 15.

Fig. 25 shows sectional views of a coupling lens and an objective lens in Example 16.

Fig. 26 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 16.

20 Fig. 27 shows sectional views of a coupling lens and an objective lens in Example 17.

Fig. 28 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 17.

Fig. 29 shows sectional views of a coupling lens and an objective lens in Example 18.

Fig. 30 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 18.

Fig. 31 shows sectional views of a coupling lens and an objective lens in Example 19.

25 Fig. 32 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 19.

Fig. 33 shows sectional views of a coupling lens and an objective lens in Example 20.

Fig. 34 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 20.

Fig. 35 shows sectional views of a coupling lens and an objective lens in Example 21.

Fig. 36 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 21.

30 Fig. 37 shows sectional views of a coupling lens and an objective lens in Example 22.

Fig. 38 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 22.

Fig. 39 shows sectional views of a coupling lens and an objective lens in Example 23.

Fig. 40 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 23.

Fig. 41 shows sectional views of a coupling lens and an objective lens in Example 24.

35 Fig. 42 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 24.

Fig. 43 shows sectional views of a coupling lens and an objective lens in Example 25.

Fig. 44 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 25.

Fig. 45 shows sectional views of a coupling lens and an objective lens in Example 26.

Fig. 46 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 26.

40 Fig. 47 shows sectional views of a coupling lens and an objective lens in Example 27.

Fig. 48 shows spherical aberration diagrams of the coupling lens and the objective lens in Example 28.

Fig. 49 shows sectional views of an objective lens in Example 28.

Fig. 50 shows aberration diagrams of the objective lens in Example 28.

Fig. 51 shows sectional views of an optical system in Example 29.

45 Fig. 52 shows an aberration diagram of the optical system in Example 29.

Fig. 53 shows sectional views of an optical system in Example 30.

Fig. 54 shows an aberration diagram of the optical system in Example 30.

Fig. 55 shows sectional views of an optical system in Example 31.

Fig. 56 shows an aberration diagram of the optical system in Example 31.

50 Fig. 57 is a diagram showing another embodiment of a optical pickup apparatus employing an objective lens of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

55 [0012] Embodiments of the invention will be explained as follows.

[0013] An aspherical single objective lens according to the first invention is an objective lens for recording on and reproducing from an information recording medium, and it is characterized to satisfy the following expression.

[0014] Incidentally, an objective lens of the invention has at least one aspherical surface. It is preferable that both

sides of the objective lens represent an aspherical surface, although it is allowable that one side only is made to be an aspherical surface. It is further preferable that an objective lens is composed of one piece of lens without being composed of plural pieces of lenses.

$$1.1 \leq d1/f \leq 3 \quad (1)$$

wherein $d1$ represents an axial lens thickness, and f represents a focal length.

[0015] The conditional expression (1) above represents conditions for obtaining excellent image height characteristics, and when trying to obtain a great numerical aperture which is not less than 0.65, or not less than 0.75 preferably, in particular, if a value of $d1/f$ is not less than the lower limit, a central thickness of a lens is not too small, image height characteristics are not deteriorated, and further, shift sensitivity does not grow greater. If a value of $d1/f$ is not more than the upper limit, the central thickness is not too large, and image height characteristics are not deteriorated. Incidentally, it is preferable that $d1$ is in a range of 2 mm - 4 mm.

[0016] Further, eccentricity sensitivity becomes excellent. In addition, spherical aberration and coma can be corrected satisfactorily. A optical pickup apparatus which reproduces or records information on an optical information recording medium of the invention has therein a light source which emits a light flux, a light converging optical system which converges a light flux emitted from the light source and a light detection unit which detects a reflected light or a transmitted light coming from an optical information recording medium. The light converging optical system has an objective lens which converges a light flux on an information recording surface of an optical information recording medium. The objective lens is one in the invention stated above. Incidentally, the light converging optical system may also have a coupling lens in addition to the objective lens. The optical information recording medium recording/reproducing apparatus of the invention has the optical pickup apparatus of the invention stated above. In addition to this, the optical information recording medium recording/reproducing apparatus may also have a spindle motor which rotates an optical information recording medium and a tracking means. Incidentally, it is preferable that a numerical aperture in the optical pickup apparatus is obtained based on a wavelength of a light source, a diameter of an aperture and a diameter of an objective lens. Incidentally, in the optical pickup apparatus, a numerical aperture which makes it possible for a light flux with prescribed wavelength to read/record information on prescribed optical information recording medium can be taken as a numerical aperture of the optical pickup apparatus, or a numerical aperture established by a standard of the optical information recording medium to be read/recorded by the optical pickup apparatus can be taken as a numerical aperture of the optical pickup apparatus. Further, when judging a numerical aperture from only a lens, if the lens is corrected to have no aberration for a range within a certain radius of an aperture of the lens (for example, the wave front aberration is corrected to be 0.07λ or less), the numerical aperture may be defined as a ratio of this radius to the focal length.

[0017] It is more desirable that the conditional expression (1) above satisfies the following expression.

$$1.2 \leq d1/f \leq 2.3$$

[0018] Further, it is most desirable that the conditional expression (1) above satisfies the following expression.

$$1.5 \leq d1/f \leq 1.8$$

[0019] Further, it is preferable that the objective lens stated above satisfies the following conditional expression (2);

$$f/vd \leq 0.060 \quad (2)$$

wherein vd represents Abbe's number.

[0020] The conditional expression (2) above represents conditions to make axial chromatic aberration small. Due to this, it is possible to cope with instantaneous wavelength fluctuations in a laser light source which can not be followed by a servomechanism for focusing, and to cope with extension of wavelength in a light source caused by multi-mode oscillation. It is desirable that the conditional expression (2) above satisfies the following expression.

$$f/vd \leq 0.050$$

[0021] Further, it is most desirable that the conditional expression (2) above satisfies the following expression.

$$f/vd \leq 0.035$$

[0022] With regard to a lens material, it is preferable that the material wherein Abbe's number preferably satisfies

EP 1 081 692 A2

vd = 50 rather than vd = 35 is used.

[0023] The objective lens may be either a glass lens or a plastic lens, but the plastic lens is more preferable. When the objective lens is a plastic lens, it is preferable that saturation water absorption of lens plastic is not more than 0.01%. Further, a material whose light transmission for light with wavelength of 350 nm - 500 nm is not less than 85% is preferable. It is preferable that a diameter of the objective lens of the invention is 2.0 mm to 4.0 mm. As a material for a plastic lens, polyolefine resins are preferable. In particular, norbornene resins are preferable.

[0024] Further, it is preferable that the objective lens stated above satisfies the following conditional expression (3);

$$1.40 \leq n \quad (3)$$

wherein, n represents a refractive index (refractive index of a material of the objective lens at the wavelength of the light source) at the wavelength used.

[0025] The conditional expression (3) above represents a condition of a refractive index, and when this condition is satisfied and a refractive index is not made small, a sag on the first surface does not grow greater, shift sensitivity and tilt sensitivity on the surface do not grow greater, and image height characteristics are not deteriorated.

[0026] Further, it is preferable that the objective lens stated above satisfies the following conditional expression (4).

$$1.40 \leq n < 1.85 \quad (4)$$

[0027] The conditional expression (4) above represents a condition of a refractive index, and in the case of an optical pickup wherein great importance needs to be attached not only to axial optical power but also to off-axial optical power, an axial thickness tends to be greater because of correction of astigmatism generated. When n is not more than the upper limit, a refractive index is not made to be too great and the central thickness of a lens does not need to be made great, which makes it easy to attain the light weight and to ensure a working distance. When n is not less than the lower limit, a refractive index is not made to be too small, a sag on the first surface does not grow greater, and image height characteristics are not deteriorated.

[0028] It is desirable that the conditional expression (4) above satisfies the following expression.

$$1.50 \leq n \leq 1.85$$

The more preferable is to satisfy the following expression.

$$1.70 \leq n < 1.85$$

[0029] Further, it is preferable that the objective lens stated above satisfies the following conditional expression (5);

$$0.40 \leq r1/(n \cdot f) \leq 0.70 \quad (5)$$

wherein, r1 represents a paraxial radius of curvature of one surface of the objective lens stated above (preferably, a paraxial radius of curvature on the part of a light source).

[0030] The conditional expression (5) above relates mainly to correction of coma, and when a value of $r1/(n \cdot f)$ is not less than the lower limit, r1 is not made to be too small, and a flare caused by introversive coma and extroversive coma becomes hard to be generated, while, when a value of $r1/(n \cdot f)$ is not more than the upper limit, r1 is not made to be too large, extroversive coma is hard to be generated, and an under flare of spherical aberration is hard to be generated.

[0031] It is desirable that the conditional expression (5) above satisfies the following expression.

$$0.40 \leq r1/(n \cdot f) \leq 0.65$$

[0032] A diameter of a spot of light converged on a recording medium by an objective lens is generally determined by $k\lambda/NA$ when λ represents a wavelength of a light source, NA represents a numerical aperture of the objective lens, and k represents a proportional constant. Therefore, when a laser light source with a small wavelength of 500 nm or less is used and a numerical aperture of the objective lens is made to be as large as 0.65 or more, it is possible to make a diameter of a spot of light to be converged to be small. It is therefore possible to make recorded information signals to be of high density, by constituting an optical pickup apparatus by the use of a lens related to the invention. Further, it is possible to provide an objective lens having a small working distance by making a protective layer of a recording medium to be as thin as 0.2 mm or less, which makes it possible to attain the light weight and compactness of an optical pickup apparatus.

EP 1 081 692 A2

[0033] In other words, the objective lens, the optical pickup apparatus and the optical information recording medium recording/reproducing apparatus, all in the invention are especially suitable when a wavelength used (wavelength of a light flux emitted from a light source) is not more than 500 nm, or when the numerical aperture of the objective lens on the optical information recording medium side is not less than 0.65 (preferably, not less than 0.7, more preferably not less than 0.75), or when they are used for an optical information recording medium having a protective layer with a thickness of 0.2 mm or less.

[0034] When the objective lens mentioned above is made of plastic materials, it is possible to attain the light weight of a optical pickup apparatus, and to realize mass production at low cost.

[0035] Another preferable aspherical single objective lens is an objective lens for recording on and reproducing from an information recording medium, and the objective lens is characterized in that a wavelength to be used is 500 nm or less, an information recording medium has a protective layer having a thickness of 0.2 mm or less, and a numerical aperture of the objective lens is 0.65 or more, and preferably is 0.75 or more.

[0036] It is preferable that the aforesaid objective lens satisfies the following conditional expression (6) representing conditions for obtaining excellent image height characteristics wherein operations thereof are the same as those in conditional expression (1);

$$1.1 \leq d1/f \leq 3 \quad (6)$$

wherein, d1 represents axial lens thickness and f represents a focal length.

[0037] It is preferable that the aforesaid objective lens satisfies the following conditional expression (7) representing conditions for making axial chromatic aberration wherein operations thereof are the same as those in conditional expression (2);

$$f/vd \leq 0.060 \quad (7)$$

wherein, vd represents Abbe's number.

[0038] It is preferable that the aforesaid objective lens satisfies the following conditional expression (8) representing conditions for a refractive index wherein operations thereof are the same as those in conditional expression (3);

$$1.40 \leq n \quad (8)$$

wherein, n represents a refractive index at the wavelength used.

[0039] It is preferable that the aforesaid objective lens satisfies the following conditional expression (9). The conditional expression (9) represents conditions for a refractive index. Operations thereof are the same as those in conditional expression (4).

$$1.40 \leq < 1.85 \quad (9)$$

[0040] It is preferable that the aforesaid objective lens satisfies the following conditional expression (10) relating mainly to correction of coma wherein operations thereof are the same as those in conditional expression (5);

$$0.40 \leq r1/(n \cdot f) \leq 0.70 \quad (10)$$

wherein, r1 represents paraxial radius of curvature on the part of a light source.

[0041] Another preferable aspherical single objective lens is an objective lens for recording on and reproducing from an information recording medium, and the objective lens is characterized in that its numerical aperture is 0.75 or more and it is made of plastic materials.

[0042] It is preferable that the aforesaid objective lens satisfies the following conditional expression (11) representing conditions for obtaining excellent image height characteristics wherein operations thereof are the same as those in conditional expression (1);

$$1.1 \leq d1/f \leq 3 \quad (11)$$

wherein, d1 represents axial lens thickness, and f represents a focal length.

[0043] It is preferable that the aforesaid objective lens satisfies the following conditional expression (12) representing conditions for making axial chromatic aberration to be small wherein operations thereof are the same as those in conditional expression (2);

EP 1 081 692 A2

$$f/v_d \leq 0.060 \quad (12)$$

wherein, v_d represents Abbe's number.

[0044] It is preferable that the aforesaid objective lens satisfies the following conditional expression (13) representing conditions for a refractive index wherein operations thereof are the same as those in conditional expression (3);

$$1.40 \leq n \quad (13)$$

wherein, n represents a refractive index at the wavelength used.

[0045] It is preferable that the aforesaid objective lens satisfies the following conditional expression (14). The conditional expression (14) represents conditions for a refractive index. Operations thereof are the same as those in conditional expression (4).

$$1.40 \leq n < 1.85 \quad (14)$$

[0046] It is preferable that the aforesaid objective lens satisfies the following conditional expression (15) relating to correction of coma wherein operations thereof are the same as those in conditional expression (5);

$$0.40 \leq r_1/(n \cdot f) \leq 0.70 \quad (15)$$

wherein, r_1 represents paraxial radius of curvature on the part of a light source.

[0047] Another preferable aspherical single objective lens is an objective lens for recording on and reproducing from an information recording medium, and the objective lens is characterized in that its numerical aperture is 0.65, and preferably is 0.75 or more and it satisfies the following expression (16);

$$n \leq 1.85 \quad (16)$$

wherein, n represents a refractive index at the wavelength used.

[0048] The conditional expression (16) above represents conditions of a refractive index. By using materials of high refractive index, it is possible to make a radius of curvature on the first surface to be large, and as a result, it is possible to make a prospective angle to be small. Thus, there is a merit that it is easy to process a metal mold when making a lens through molding. Further, in the case of an optical pickup wherein great importance needs to be attached only to axial optical power, the use of materials of high refractive index makes it easy to correct spherical aberration of a high order.

[0049] It is preferable that the aforesaid objective lens satisfies the following conditional expression (17) representing conditions for obtaining excellent image height characteristics wherein operations thereof are the same as those in conditional expression (1);

$$1.1 \leq d_1/f \leq 3 \quad (17)$$

wherein, d_1 represents axial lens thickness and f represents a focal length.

[0050] It is preferable that the aforesaid objective lens satisfies the following conditional expression (18) relating to correction of coma wherein operations thereof are the same as those in conditional expression (5);

$$0.40 \leq r_1/(n \cdot f) \leq 0.70 \quad (18)$$

wherein, r_1 represents paraxial radius of curvature on the part of a light source.

[0051] Another aspherical single objective lens is an objective lens for recording on and reproducing from an information recording medium, and the objective lens is characterized in that its numerical aperture is 0.65, and preferably is 0.75 or more and it satisfies the following expression (19);

$$1.40 \leq n < 1.85 \quad (19)$$

wherein, n represents a refractive index at the wavelength used.

[0052] The aforesaid conditional expression represents conditions of a refractive index. In respect to its operations, they are the same as those in expression (4).

[0053] It is preferable to provide a diffraction section on a light converging optical system in the optical pickup apparatus of the invention. Though it is preferable to provide a diffraction section on an objective lens of the light converging

optical system, it is possible either to incorporate an optical element having only a diffraction section in the light converging optical system or to provide a diffraction section on another optical element which constitutes a light converging optical system such as a coupling lens. Incidentally, it is also possible to provide a diffraction surface only on one side of a single coupling lens. Owing to this structure, it is possible to prevent deterioration of wavefront aberration caused by surface eccentricity.

[0054] When spherical aberration is corrected for the standard wavelength by only a spherical surface or by only an aspherical surface, for a single objective lens in a refraction system, there is normally generated under axial chromatic aberration for the wavelength that is shorter than the standard wavelength, and over axial chromatic aberration for the wavelength that is longer than the standard wavelength. However, in the case of the objective lens having a diffraction surface, when spherical aberration is corrected for the standard wavelength, it is possible to generate polarity which is opposite to the objective lens in a refraction system, namely, to generate over axial chromatic aberration for the wavelength that is shorter than the standard wavelength and under axial chromatic aberration for the wavelength that is longer than the standard wavelength. Therefore, in the case of the objective lens stated above, it is possible to realize an objective lens which shows excellent performance even for instantaneous wavelength fluctuations such as mode hop, for example, by combining diffraction powers through appropriate selection of the aspheric surface coefficient as an aspherical lens and a coefficient of a phase function as a diffraction lens, and thereby by correcting chromatic aberration for the spherical aberration.

[0055] The objective lens stated above has a numerical aperture of 0.65 or more, or preferably of 0.75 or more, and when a wavelength to be used is 500 nm or less, and when an information recording medium wherein a thickness of a protective layer is 0.2 mm or less is used, it is possible to use a laser light source having a short wavelength of not more than 500 nm, to make a numerical aperture of the objective lens to be as large as 0.65 or more, and to make a spot diameter of light to be converged to be small. Thus, it is possible to realize high density of recorded information signals, by constituting an optical pickup apparatus with a lens of the invention. Further, it is possible to provide an objective lens having a small working distance, by making a protective layer of a recording medium to be as thin as 0.2 mm or less, which makes it possible to attain the light weight and compactness of an optical pickup apparatus.

[0056] Further, in each objective lens mentioned above, it is preferable that a flange portion is provided on the outer circumference, and it is more preferable that there is provided on the outer circumference a flange portion having a surface extending in the direction perpendicular to an optical axis. Due to the flange portion provided on the outer circumference, the objective lens can be attached on the optical pickup apparatus easily, and it is possible to attach the objective lens more accurately by providing on the flange portion a surface extending in the direction almost perpendicular to an optical axis.

[0057] Further, each optical pickup apparatus of the invention is one having therein a light source and an objective lens which converges a light flux from the light source on the information recording surface of an information recording medium, and conducting information recording on the information recording medium and/or information reproducing therefrom, through detection of light from the information recording medium, wherein an aspherical single objective lens is provided as the objective lens mentioned above.

[0058] Further, each optical pickup apparatus of the invention is one having therein a light source, a coupling lens which changes a divergence angle of a divergent light emitted from the light source, and an objective lens which converges a light flux through the coupling lens on the information recording surface of an information recording medium, and conducting information recording on the information recording medium and/or information reproducing therefrom, through detection of light from the information recording medium, wherein the coupling lens has functions to correct chromatic aberration of the objective lens, and the aspherical single objective lens is provided as the objective lens mentioned above.

[0059] When an aspherical single objective lens is used as an objective lens, it is possible to obtain the objective lens suitable for a high density recording/reproducing apparatus, but there is caused axial chromatic aberration which is under on the part of a short wavelength, because of the single objective lens in a refraction system. However, the axial chromatic aberration can be corrected by the coupling lens in the aforesaid optical pickup apparatus. Namely, if axial chromatic aberration of the coupling lens is made to be over on the part of a short wavelength, axial chromatic aberration of the objective lens can be reduced. Due to this, together with the objective lens mentioned above, it is possible to obtain an optical pickup apparatus having an optical system wherein axial chromatic aberration is corrected by the simple structure.

[0060] In this case, the coupling lens can collimate a light flux emitted from the light source to the mostly collimated light flux. This structure makes assembly and adjustment of a pickup optical system to be simple. Namely, the coupling lens may also be a collimator lens.

[0061] It is further possible to arrange so that chromatic aberration of a composition system of the objective lens and the coupling lens may satisfy the following expression (20);

$$\delta f_b \cdot NA^2 \leq 0.25 \mu m \quad (\delta f_b > 0) \quad (20)$$

wherein δf_b represents a change of focal position (μm) of the composition system when a wavelength is changed from the standard wavelength by +1 nm, and NA represents a numerical aperture of the objective lens on the part of a disk.

[0062] It is more preferable that the following expression (20)' is satisfied.

$$0.02 \mu\text{m} \leq \delta f_b \cdot \text{NA}^2 \leq 0.15 \mu\text{m} \quad (\delta f_b > 0) \quad (20)'$$

[0063] Each structure stated above is one relating to the correction of chromatic aberration carried out by the coupling lens. When handling a short wavelength laser semiconductor with oscillation wavelength of about 400 nm, axial chromatic aberration caused on the objective lens by the microscopic shift of wavelength is an unallowable serious problem. The causes for the problem are given as follows. When handling a short wavelength, a change in refractive index for ordinary lens materials is large for microscopic fluctuation of a wavelength. As a result, a defocusing amount for the focus is large. With regard to a focal depth of the objective lens, however, the shorter the wavelength (λ) to be used is, the smaller the focal depth is, as is understood from $k\lambda/\text{NA}^2$ (k is a proportional constant), and even a very small amount of defocusing is not allowed. In Session WD26 of ISOM/ODS'99 Postdeadline Poster Papers, high frequency superimposition with spectrum width of 0.7 nm (FWMH) is shown for GaN blue semiconductor laser. It is desirable to control wave front aberration of a pickup optical system to about $0.02 \lambda_{\text{rms}}$ for the high frequency superimposition. A level of correction of axial chromatic aberration necessary for the foregoing was obtained, on the assumption that spherical aberration for color has been corrected. Whereupon, it was necessary to control the axial chromatic aberration of the composition system within about $0.15 \mu\text{m}/\text{NA}^2$ for wavelength fluctuation of 1 nm, for controlling wave front aberration to $0.02 \lambda_{\text{rms}}$ for the high frequency superimposition with spectrum width of 0.7 nm (FWMH), when the standard wavelength is 400 nm and NA represents a numerical aperture on the part of a disk. On the other hand, the axial chromatic aberration of the composition system does not always need to be corrected perfectly, and wave front aberration can remain in an allowable range. When the objective lens is a single lens in a refraction system as in the invention, it is possible to constitute a coupling lens in a simple way by leaving the axial chromatic aberration to be a positive value for a long wavelength even in the composition system, because the axial chromatic aberration is of a positive value for the long wavelength for the objective lens. For example, when a coupling lens is composed of a one-group and two-element cemented lens, power of each lens element of the coupling lens can be weak, compared with perfect color correction of the composition system, resulting in a coupling lens which is excellent in terms of aberration and is easy to make. Even in the case of correcting color for a coupling lens as a diffraction lens, power of a diffraction surface can be weak, thus, an interval of zonal diffraction rings is large, and a diffraction lens with high diffraction efficiency can easily be manufactured. For this reason, the lower limit of the aforesaid conditional expression was established.

[0064] Further, it is preferable to satisfy the following expression concerning magnification m of a composition system;

$$0.1 \leq |m| \leq 0.5 \quad (m < 0)$$

wherein, m represents magnification of a composition system of an objective lens and a coupling lens.

[0065] When the magnification is not lower than the lower limit of the conditional expression above, the composition system is compact, while, when the magnification is not higher than the upper limit, the coupling lens is better in terms of aberration.

[0066] The coupling lens may be composed either of one piece or of plural pieces, and it is preferable that the coupling lens is of the one-group and two-element structure. Due to the one-group and two-element structure of the coupling lens stated above, the structure of the coupling lens is simple and it causes manufacture of the coupling lens to be easy. When using a one-group and two-element coupling lens, it is possible to generate sharply the axial chromatic aberration which is over on the part of a short wavelength and is under on the part of a long wavelength, while keeping the axial power. As a result, it is possible to correct favorably the axial chromatic aberration on the objective lens which is under on the part of a short wavelength and is over on the part of a long wavelength, while keeping the axial power on the composition system, which is advantageous for instantaneous wavelength fluctuations such as mode hop. When this axial chromatic aberration is made to be over on the part of a short wavelength and to be under on the part of a long wavelength, the curvature on the cemented surface of the coupling lens having diverging actions tends to be great. Therefore, if spherical aberration at the standard wavelength is controlled, spherical aberration which is over on the part of a short wavelength and is under on the part of a long wavelength is generated greatly. As a result, spherical aberrations on the part of a short wavelength and on the part of a long wavelength generated on the objective lens are canceled, and spherical aberration of a composition system in the case of wavelength fluctuations can be controlled to be small.

[0067] Incidentally, it is preferable that the coupling lens has an aspherical surface. The aspherical surface can be provided either on one side or on both sides.

[0068] Since the coupling lens stated above is of a one-group and two-element structure having an aspheric sur-

face, it is possible to make a numerical aperture of the coupling lens to be large by aberration correction functions of the aspheric surface and to obtain a compact composition system whose total length is short.

[0069] Since the coupling lens stated above has a diffraction surface, it is possible to obtain a highly efficient coupling lens with a simple structure of a single lens, by adding, in particular, a diffraction surface to a plastic aspherical lens. Incidentally, it is also possible to correct fluctuations of spherical aberration caused on each optical surface of an optical system, by moving a coupling lens in the optical axis direction. For example, a coupling lens may be moved while monitoring RF amplitude of a reproduction signal, so that spherical aberration caused in the optical system may be corrected in an optimal way. As fluctuations of spherical aberration caused on each optical surface of an optical system, there are given, as an example, the fluctuation based on minute changes in oscillation wavelength of a light source, the fluctuation based on temperature change, the fluctuation based on humidity change, the fluctuation based on minute change in a thickness of a protective layer of an information recording medium and the fluctuation based on combination of the foregoing. It is preferable that a coupling lens is shifted in the optical axis direction so that a distance from an objective lens may be increased when spherical aberration of an optical system fluctuates to the greater side, and a coupling lens is shifted in the optical axis direction so that a distance from an objective lens may be decreased when spherical aberration of an optical system fluctuates to the smaller side. Incidentally, with regard to a movement of the coupling lens in the optical axis direction, it is preferable that an optical pickup apparatus has a shifting unit which shifts the coupling lens. As a shifting unit, a voice-coil-shaped actuator and a piezo-actuator can be used.

[0070] Incidentally, each optical pickup apparatus mentioned above converges a light flux emitted from a laser light source through the objective lens on the information recording surface of an information recording medium, and it can conduct recording of information on the information recording medium and/or reproducing of information from the information recording medium.

[0071] The optical information recording medium stated above includes, for example, various CDs such as CD, CD-R, CD-RW, CD-Video and CD-ROM, various DVDs such as DVD, DVD-ROM, DVD-RAM, DVD-R and DVD-RW, and a disk-shaped information recording medium such as MD, and further, a novel high density information recording medium that has been enhanced in terms of recording density is included.

[0072] Embodiments of the invention will be explained as follows, referring to the drawings. Fig. 8 is a schematic structure diagram of an optical pickup apparatus showing an embodiment of the invention.

[0073] An optical pickup apparatus in Fig. 8 is one employing the double aspherical single objective lens of the invention as an objective lens, wherein semiconductor laser 3 representing a light source, coupling lens 2 which changes a divergence angle of a divergent light emitted from the light source 3, objective lens 1 which converges a light flux coming from the coupling lens 2 on information recording surface 5 of an information recording medium, and photo-detector 4 which receives reflected light from information recording surface 5 of an information recording medium are provided.

[0074] The optical pickup apparatus in Fig. 8 is further provided with beam splitter 6 which splits the reflected light from information recording surface 5 toward the photo-detector 4, 1/4 wavelength plate 7 located between coupling lens 2 and objective lens 1, diaphragm 8 located to be ahead of objective lens 1, cylindrical lens 9 and actuator 10 for focus tracking. In other words, in the present embodiment, the light converging optical system has therein a beam splitter, a coupling lens, a 1/4 wavelength plate, an objective lens and a diaphragm. Incidentally, in the present embodiment, the beam splitter may be regarded as one which is not included in a light converging optical system.

[0075] Objective lens 1 further has, on its outer circumference, flange portion 1a having a surface extending in the direction perpendicular to the optical axis. Due to this flange portion 1a, objective lens 1 can be attached accurately on the optical pickup apparatus.

[0076] The coupling lens 2 may also be a collimating lens which collimates an incident divergent light flux to be a light flux that is almost in parallel with an optical axis. In this case, it is preferable that light source 3 or collimating lens 2 is arranged to be movable in the direction of an optical axis of the collimating lens for adjustment so that a light flux emerging from the collimating lens 2 may nearly be collimated.

[0077] As stated above, the optical pickup apparatus of the invention may either be composed of a collimating lens for converting a divergent light flux from a light source into a mostly collimated light and of an objective lens for converging the collimated light on an information recording surface, or be composed of a coupling lens representing a converting lens which changes an angle of a divergent light flux from a light source and converts into a diverged light flux or a converged light flux and of an objective lens which converges a light flux emerging from the coupling lens on an information recording surface. The optical pickup apparatus may further be composed only of an objective lens (finite conjugational objective lens) for converging a divergent light flux from a light source on an information recording surface.

[0078] Then, it is possible to obtain an optical pickup apparatus capable of conducting high density recording and reproducing for an optical disk, by using an aspherical single objective lens of the invention for the aforesaid optical pickup apparatus. Example

[0079] Next, there will be explained Examples 1 - 15 each being for an objective lens and an optical pickup apparatus both of the invention and Examples 16 - 27 each being for a coupling lens and a coupling lens and an optical pickup apparatus. Incidentally, an example of the schematic structure of the optical pickup apparatus is like what is shown in

EP 1 081 692 A2

Fig. 8 explained in an embodiment. The optical pickup apparatus of the invention was obtained by conducting selection of the standard wavelength of a semiconductor laser (setting of a light source), establishment such as usage or elimination of a coupling lens or usage of a collimating lens as a coupling lens, establishment of an aperture of diaphragm 8 and establishment of positions for arranging various parts, and by mounting an objective lens and a coupling lens of each example, so that the structures and conditions described in each example below may be satisfied.

[0080] First, an example of an objective lens will be explained. A list of data of Examples 1 - 15 is shown in Table 1 below. Incidentally, in Examples 1 - 15, Examples 6, 9 and 15 are for a plastic lens, and others are for a glass lens. An optical information recording medium in Example 5 has no transparent substrate. Each of optical information recording media in other Examples has a 0.1 mm-thick transparent

Table 1

List of Examples		1	2	3	4	5
f		1.76	1.76	1.76	1.76	0.13
NA		0.85	0.75	0.85	0.75	0.83
Wavelength (nm)		400	400	400	400	660
d1/f		1.79	1.73	1.68	1.59	1.74
f/vd		0.048	0.048	0.033	0.033	0.003
vd		37.0	37.0	53.2	53.2	40.9
r1/(n · f)		0.53	0.53	0.50	0.50	0.49
n		1.85614	1.85614	1.71667	1.71667	1.79998
Wave front aberration (λ rms)	Axial	0.010	0.005	0.012	0.006	0.003
	Off-axis	0.054	0.029	0.060	0.033	0.019
	(Image height)	(0.03mm)	(0.03mm)	(0.03mm)	(0.03mm)	(0.005mm)
	(Angle of view)	(1°)	(1°)	(1°)	(1°)	(2°)
List of Examples		6	7	8	9	10
f		2.65	1.76	1.76	1.76	1.76
NA		0.85	0.85	0.85	0.85	0.85
Wavelength (nm)		400	400	405	405	405
d1/f		1.79	1.42	1.56	1.47	1.51
f/vd		0.047	0.048	0.033	0.030	0.019
vd		56.0	37.0	53.2	59.5	95.0
r1/(n · f)		0.48	0.47	0.47	0.44	0.42
n		1.56119	1.85614	1.71558	1.52523	1.44260
Wave front aberration (λ rms)	Axial	0.022	0.005	0.008	0.008	0.014
	Off-axis	0.121	0.070	0.063	0.098	0.118
	(Image height)	(0.03mm)	(0.03mm)	(0.03mm)	(0.03mm)	(0.03mm)
	(Angle of view)	(0.6°)	(1°)	(1°)	(1°)	(1°)

EP 1 081 692 A2

Table 1 (continued)

List of Examples		11	12	13	14	15
f		1.76	1.76	1.76	1.76	1.76
NA		0.85	0.85	0.85	0.85	0.85
Wavelength (nm)		405	405	405	405	405
d1/f		1.50	1.36	2.07	2.22	1.43
f/vd		0.022	0.083	0.083	0.106	0.030
vd		81.6	21.2	21.2	16.6	59.5
r1/(n · f)		0.44	0.44	0.60	0.64	0.46
n		1.50716	2.15857	2.15857	2.34860	1.52523
Wave front aberration (λ rms)	Axial	0.009	0.002	0.006	0.006	0.010
	Off-axis	0.106	0.112	0.032	0.030	0.081
	(Image height)	(0.03mm)	(0.03mm)	(0.03mm)	(0.03mm)	(0.03mm)
	(Angle of view)	(1°)	(1°)	(1°)	(1°)	(1°)

[0081] An objective lens in Examples 1 - 4 and Examples 6 and 7 is an infinite objective lens for the standard wavelength of 400 nm, and an objective lens in Examples 8 - 15 and Examples 6 and 7 is an infinite objective lens for the standard wavelength of 405 nm. In each of Examples 6 and 9, a protective layer of an information recording medium having a thickness of 0.1 mm is assumed to be positioned and a working distance of not less than 0.1 mm is provided between an objective lens and an image surface of an information recording medium, and plastic materials are used for the objective lens. An objective lens in Example 5 is an infinite objective lens for the standard wavelength of 660 nm. Example 15 is one wherein a diffraction section is provided. Incidentally, the term described as "Off-axis" of "Wave front aberration" in Table 1 shows image height characteristics. Table 1 shows that image height characteristics in Example 1 - Example 15 are excellent. In Example 8, wave front aberration caused by the first surface that is decentered by 1 μm is 0.021 λ which makes eccentricity sensitivity to be excellent because it is smaller than 0.035 λ. It was possible to make eccentricity sensitivity to be excellent even in other Examples. With regard to an aspherical surface in the present example, it is expressed by the following expression when an x-axis is represented by the direction of an optical axis, a height in the direction perpendicular to the optical axis is represented by h, and a radius of curvature of the surface is represented by r, on the assumption that K represents a constant of the cone and A_{2i} represents an aspherical surface coefficient.

$$x = \frac{h^2/r}{1 + \sqrt{1 - (1+K)h^2/r^2}} + \sum_{i=2} A_{2i} h^{2i}$$

Example 1 Lens data are shown in Table 2, and aspherical surface coefficients are shown in Table 3. The lens of Example 1 is shown in Fig. 1 wherein Fig. 1 (a) is a sectional view and Fig. 1 (b) is an aberration diagram.

[0082]

λ (wavelength) = 400 nm

f = 1.765 mm

NA = 0.85

Magnification = 0

EP 1 081 692 A2

[0083]

Table 2

	r(mm)	d(mm)	n	vd
1*	1.72078	3.150	1.85614	37.0
2*	-1.92753	0.213		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

Table 3

Aspherical surface coefficient	
First surface	Second surface
K=-0.319957	K=-126.71803
$A_4 = -0.897201 \times 10^{-3}$	$A_4 = 0.446627 \times 10^{-1}$
$A_6 = -0.132966 \times 10^{-2}$	$A_6 = -0.374370 \times 10^{-1}$
$A_8 = 0.567005 \times 10^{-3}$	$A_8 = 0.128630 \times 10^{-1}$
$A_{10} = -0.488314 \times 10^{-3}$	$A_{10} = -0.176551 \times 10^{-1}$
$A_{12} = 0.337127 \times 10^{-4}$	$A_{12} = 0.252229 \times 10^{-3}$
$A_{14} = 0.426690 \times 10^{-4}$	
$A_{16} = -0.200712 \times 10^{-4}$	

35 (Example 2)

[0084] Lens data are shown in Table 4, and aspherical surface coefficients are shown in Table 5. The lens of Example 2 is shown in Fig. 2 wherein Fig. 2 (a) is a sectional view and Fig. 2 (b) is an aberration diagram.

λ (wavelength) = 400 nm

f = 1.765 mm

NA = 0.75

Magnification = 0

Table 4

	r(mm)	d(mm)	n	vd
1*	1.72793	3.037	1.85614	37.0
2*	-2.27646	0.272		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

Table 5

Aspherical surface coefficient	
First surface	Second surface
$K=-0.332121$	$K=-87.525272$
$A_4=-0.142338 \times 10^{-2}$	$A_4 = 0.378863 \times 10^{-1}$
$A_6=-0.145971 \times 10^{-2}$	$A_6 = -0.330567 \times 10^{-1}$
$A_8 = 0.480431 \times 10^{-3}$	$A_8 = 0.125735 \times 10^{-2}$
$A_{10}=-0.506544 \times 10^{-3}$	$A_{10}=-0.193685 \times 10^{-2}$
$A_{12}= 0.213333 \times 10^{-4}$	$A_{12}=-0.252229 \times 10^{-3}$
$A_{14}= 0.180460 \times 10^{-4}$	
$A_{16}=0.104472 \times 10^{-4}$	

(Example 3)

[0085] Lens data are shown in Table 6, and aspherical surface coefficients are shown in Table 7. The lens of Example 3 is shown in Fig. 3 wherein Fig. 3 (a) is a sectional view and Fig. 3 (b) is an aberration diagram.

 λ (wavelength) = 400 nm

f=1.765 mm

NA = 0.85

Magnification = 0

Table 6

	r(mm)	d(mm)	n	vd
1*	1.51143	2.946	1.71667	53.2
2*	-1.44415	0.267		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

Table 7

Aspherical surface coefficient	
First surface	Second surface
$K=-0.435901$	$K=-59.503252$
$A_4 = 0.227660 \times 10^{-2}$	$A_4 = 0.330895 \times 10^{-1}$
$A_6=-0.331034 \times 10^{-2}$	$A_6 = -0.173954 \times 10^{-1}$
$A_8 = 0.363944 \times 10^{-2}$	$A_8 = 0.376531 \times 10^{-1}$
$A_{10}=-0.258170 \times 10^{-2}$	$A_{10}=-0.327613 \times 10^{-1}$
$A_{12}= 0.676932 \times 10^{-3}$	$A_{12}=-0.252229 \times 10^{-3}$
$A_{14}= 0.153229 \times 10^{-4}$	

EP 1 081 692 A2

Table 7 (continued)

Aspherical surface coefficient	
First surface	Second surface
$A_{16} = -0.463776 \times 10^{-4}$	

(Example 4)

[0086] Lens data are shown in Table 8, and aspherical surface coefficients are shown in Table 9. The lens of Example 4 is shown in Fig. 4 wherein Fig. 4 (a) is a sectional view and Fig. 4 (b) is an aberration diagram.

λ (wavelength) = 400 nm

$f = 1.765$ mm

NA = 0.75

Magnification = 0

Table 8

	r(mm)	d(mm)	n	vd
1*	1.51629	2.801	1.71667	53.2
2*	-1.74496	0.342		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

Table 9

Aspherical surface coefficient	
First surface	Second surface
$K = -0.448813$	$K = -46.678777$
$A_4 = 0.580310 \times 10^{-3}$	$A_4 = 0.219283 \times 10^{-1}$
$A_6 = -0.158678 \times 10^{-2}$	$A_6 = -0.124381 \times 10^{-1}$
$A_8 = 0.136862 \times 10^{-2}$	$A_8 = 0.291780 \times 10^{-1}$
$A_{10} = -0.198562 \times 10^{-2}$	$A_{10} = -0.280227 \times 10^{-1}$
$A_{12} = 0.114053 \times 10^{-2}$	$A_{12} = -0.252229 \times 10^{-3}$
$A_{14} = -0.438727 \times 10^{-3}$	
$A_{16} = 0.508367 \times 10^{-4}$	

(Example 5)

[0087] Lens data are shown in Table 10, and aspherical surface coefficients are shown in Table 11. The lens of Example 5 is shown in Fig. 5 wherein Fig. 5 (a) is a sectional view and Fig. 5 (b) is an aberration diagram.

λ (wavelength) = 660 nm

$f = 0.131$ mm

NA = 0.83

Magnification = -0.1456

EP 1 081 692 A2

Table 10

	r(mm)	d(mm)	n	vd
1*	0.115	0.226	1.79998	40.9
2*	-0.147	0.000		

*: Aspherical surface

Table 11

Aspherical surface coefficient	
First surface	Second surface
K=-0.3946	K=-77.181
$A_4 = -0.78479 \times 10^{-4}$	$A_4 = 0.24008 \times 10^{-2}$
$A_6 = -0.23519 \times 10^{-4}$	$A_6 = -0.10585 \times 10^{-5}$
$A_8 = 0.56266 \times 10^{-5}$	$A_8 = 0.93242 \times 10^{-6}$
$A_{10} = -0.27400 \times 10^{-7}$	$A_{12} = -0.10004 \times 10^{-10}$
$A_{12} = -0.20657 \times 10^{-9}$	
$A_{14} = 0.75407 \times 10^{-7}$	
$A_{16} = -0.35744 \times 10^{-11}$	

(Example 6)

[0088] Lens data are shown in Table 12, and aspherical surface coefficients are shown in Table 13. The lens of Example 6 is shown in Fig. 6 wherein Fig. 6 (a) is a sectional view and Fig. 6 (b) is an aberration diagram.

λ (wavelength) = 400 nm
 $f = 2.647$ mm
 NA = 0.85
 Magnification = 0

Table 12

	r(mm)	d(mm)	n	vd
1*	1.97771	4.748	1.56119	56.0
2*	-0.81768	0.300		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

EP 1 081 692 A2

Table 13

Aspherical surface coefficient	
First surface	Second surface
K=-0.576418	K=-19.183803
$A_4 = 0.265281 \times 10^{-2}$	$A_4 = 0.335865 \times 10^{-1}$
$A_6 = -0.413751 \times 10^{-3}$	$A_6 = -0.922525 \times 10^{-1}$
$A_8 = 0.317393 \times 10^{-3}$	$A_8 = 0.116730 \times 10^{-1}$
$A_{10} = -0.591851 \times 10^{-4}$	$A_{10} = -0.591738 \times 10^{-1}$
$A_{12} = -0.442060 \times 10^{-5}$	$A_{12} = -0.291540 \times 10^{-5}$
$A_{14} = 0.362723 \times 10^{-5}$	
$A_{16} = -0.412233 \times 10^{-6}$	

(Example 7)

[0089] Lens data are shown in Table 14, and aspherical surface coefficients are shown in Table 15. The lens of Example 7 is shown in Fig. 7 wherein Fig. 7 (a) is a sectional view and Fig. 7 (b) is an aberration diagram.

λ (wavelength) = 400 nm
 $f = 1.765$ mm
 $NA = 0.85$
 Magnification = 0

Table 14

	r(mm)	d(mm)	n	vd
1*	1.53773	2.500	1.85614	37.0
2*	-21.60833	0.380		
3	∞	0.100	1.62158	30.0
4	∞	0.000		

*:Aspherical surface

Table 15

Aspherical surface coefficient	
First surface	Second surface
K=-0.329489	K= 199.72542
$A_4 = -0.168113 \times 10^{-2}$	$A_4 = 0.344557 \times 10^{-1}$
$A_6 = -0.913997 \times 10^{-3}$	$A_6 = -0.119299 \times 10^{-1}$
$A_8 = -0.127668 \times 10^{-3}$	$A_8 = 0.181507 \times 10^{-1}$
$A_{10} = -0.319026 \times 10^{-3}$	$A_{10} = -0.110457 \times 10^{-1}$
$A_{12} = 0.691773 \times 10^{-4}$	$A_{12} = -0.252229 \times 10^{-3}$
$A_{14} = -0.241646 \times 10^{-4}$	

EP 1 081 692 A2

Table 15 (continued)

Aspherical surface coefficient	
First surface	Second surface
$A_{16} = -0.187683 \times 10^{-4}$	

(Example 8)

[0090] Lens data and aspherical surface coefficients are shown in Table 16. A sectional view of the objective lens of Example 8 is shown in Fig. 9, and an aberration diagram thereof is shown in Fig. 10.

Table 16

Example 8

$\lambda = 405 [\text{nm}]$

$f = 1.765 [\text{mm}]$

$\text{NA} = 0.85$

Magnification = 0

	$r (\text{mm})$	$d (\text{mm})$	n	vd
1*	1.43376	2.750	1.71558	53.2
2*	-2.11753	0.290		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
$K = -0.452646$	$K = -185.75159$
$A_4 = 0.571669\text{E-}02$	$A_4 = 0.281279\text{E+}00$
$A_6 = -0.591147\text{E-}02$	$A_6 = -0.742134\text{E+}00$
$A_8 = 0.721339\text{E-}02$	$A_8 = 0.667680\text{E+}00$
$A_{10} = -0.398819\text{E-}02$	$A_{10} = -0.195290\text{E+}00$
$A_{12} = 0.390519\text{E-}03$	$A_{12} = -0.252228\text{E-}03$
$A_{14} = 0.446956\text{E-}03$	
$A_{16} = -0.135385\text{E-}03$	

(Example 9)

[0091] Lens data and aspherical surface coefficients are shown in Table 17. A sectional view of the objective lens of Example 9 is shown in Fig. 11, and an aberration diagram thereof is shown in Fig. 12.

Table 17

Example 9

$$\lambda = 405[\text{nm}]$$

$$f = 1.765[\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r(mm)	d(mm)	n	vd
1*	1.17503	2.602	1.52523	59.5
2*	-1.04152	0.357		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.682004	K=-29.373780
A ₄ = 0.180213E-01	A ₄ = 0.297543E+00
A ₆ = 0.368416E-02	A ₆ = -0.423018E+00
A ₈ = 0.140365E-02	A ₈ = 0.295535E+00
A ₁₀ = 0.342876E-03	A ₁₀ = -0.829290E-01
A ₁₂ = -0.311534E-04	A ₁₂ = -0.252257E-03
A ₁₄ = 0.103341E-03	
A ₁₆ = 0.141728E-04	

(Example 10)

[0092] Lens data and aspherical surface coefficients are shown in Table 18. A sectional view of the objective lens of Example 10 is shown in Fig. 13, and an aberration diagram thereof is shown in Fig. 14.

Table 18

Example 10

$\lambda = 405[\text{nm}]$
 $f = 1.765[\text{mm}]$
 $\text{NA} = 0.85$
Magnification = 0

	r (mm)	d (mm)	n	vd
1*	1.07547	2.657	1.44260	95.0
2*	-0.69088	0.366		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.700141	K=-12.891107
A ₄ = 0.190496E-01	A ₄ = 0.262567E+00
A ₆ = 0.502475E-02	A ₆ = -0.355053E+00
A ₈ = 0.115240E-02	A ₈ = 0.236709E+00
A ₁₀ = 0.134395E-03	A ₁₀ = -0.631951E-01
A ₁₂ = 0.369702E-04	A ₁₂ = -0.253345E-03
A ₁₄ = 0.315362E-03	
A ₁₆ = -0.398715E-04	

(Example 11)

[0093] Lens data and aspherical surface coefficients are shown in Table 19. A sectional view of the objective lens of Example 11 is shown in Fig. 15, and an aberration diagram thereof is shown in Fig. 16.

Table 19

Example 11

$$\lambda = 405[\text{nm}]$$

$$f = 1.765[\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r(mm)	d(mm)	n	vd
1*	1.15821	2.647	1.50716	81.6
2*	-0.90947	0.346		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.661186	K=-24.300945
A ₄ = 0.159215E-01	A ₄ = 0.296712E+00
A ₆ = 0.483822E-02	A ₆ = -0.416550E+00
A ₈ = -0.630221E-03	A ₈ = 0.289015E+00
A ₁₀ = 0.130734E-02	A ₁₀ = -0.807695E-01
A ₁₂ = -0.585454E-04	A ₁₂ = -0.252243E-03
A ₁₄ = -0.503797E-04	
A ₁₆ = 0.569157E-04	

(Example 12)

[0094] Lens data and aspherical surface coefficients are shown in Table 20. A sectional view of the objective lens of Example 12 is shown in Fig. 17, and an aberration diagram thereof is shown in Fig. 18.

Table 20

Example 12

$$\lambda = 405[\text{nm}]$$

$$f = 1.765[\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r(mm)	d(mm)	n	vd
1*	1.69377	2.400	2.15857	21.2
2*	2.36431	0.361		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.413733	K=-9.944350
A ₄ = 0.330545E-02	A ₄ = 0.834366E-01
A ₆ = -0.226795E-03	A ₆ = -0.534921E+00
A ₈ = 0.133470E-02	A ₈ = 0.647444E+00
A ₁₀ = -0.133780E-02	A ₁₀ = -0.195829E+00
A ₁₂ = 0.654514E-03	A ₁₂ = -0.252217E-03
A ₁₄ = -0.152871E-03	
A ₁₆ = 0.488831E-05	

(Example 13)

[0095] Lens data and aspherical surface coefficients are shown in Table 21. A sectional view of the objective lens of Example 13 is shown in Fig. 19, and an aberration diagram thereof is shown in Fig. 20.

Table 21

Example 13

$$\lambda = 405[\text{nm}]$$

$$f = 1.765[\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r(mm)	d(mm)	n	vd
1*	2.30000	3.650	2.15857	21.2
2*	-2.73024	0.200		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.456357	K=-219.93144
A ₄ = 0.712833E-03	A ₄ = -0.962060E-01
A ₆ = -0.604365E-03	A ₆ = -0.200434E+00
A ₈ = 0.898662E-03	A ₈ = 0.741851E+00
A ₁₀ = -0.133726E-02	A ₁₀ = -0.292121E+00
A ₁₂ = 0.785181E-03	A ₁₂ = -0.252226E-03
A ₁₄ = -0.223083E-03	
A ₁₆ = 0.199958E-04	

(Example 14)

[0096] Lens data and aspherical surface coefficients are shown in Table 22. A sectional view of the objective lens of Example 14 is shown in Fig. 21, and an aberration diagram thereof is shown in Fig. 22.

Table 22

Example 14

$$\lambda = 405[\text{nm}]$$

$$f = 1.765[\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r (mm)	d (mm)	n	vd
1*	2.64228	3.919	2.34860	16.6
2*	-3.55612	0.200		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

*: Aspherical surface

Aspherical surface coefficient	
First surface	Second surface
K=-0.467576	K=-321.19491
A ₄ = 0.555792E-03	A ₄ = -0.195720E+00
A ₆ = -0.149475E-02	A ₆ = 0.310925E+00
A ₈ = 0.178501E-02	A ₈ = -0.244958E+00
A ₁₀ = -0.157718E-02	A ₁₀ = 0.486778E-01
A ₁₂ = 0.651169E-03	A ₁₂ = -0.252220E-03
A ₁₄ = -0.127250E-03	
A ₁₆ = 0.484981E-05	

(Example 15)

[0097] Lens data and aspherical surface coefficients are shown in Table 23. A sectional view of the objective lens of Example 15 is shown in Fig. 23, and an aberration diagram thereof is shown in Fig. 24.

Table 23

Example 15

$$\lambda = 405 [\text{nm}]$$

$$f = 1.765 [\text{mm}]$$

$$\text{NA} = 0.85$$

$$\text{Magnification} = 0$$

	r (mm)	d (mm)	n	vd
1 (Aspherical surface 1, Diffraction surface 1)	1.23647	2.532	1.52523	59.5
2 (Aspherical surface 2)	-1.18419	0.336	1.61950	30.0
3	∞	0.100		
4	∞	0.000		

Aspherical surface 1	Diffraction surface 1
K=-0.68816	b ₂ = -0.20985E-01
A ₄ = 0.17621E-01	b ₄ = -0.26478E-02
A ₆ = 0.32160E-02	b ₆ = -0.31346E-03
A ₈ = 0.17762E-02	b ₈ = -0.63327E-04
A ₁₀ = 0.28747E-03	b ₁₀ = -0.45002E-04
A ₁₂ = -0.17669E-03	b ₁₂ = -0.20458E-04
A ₁₄ = 0.94949E-04	b ₁₄ = -0.10510E-04
A ₁₆ = 0.17955E-04	b ₁₆ = 0.36615E-05

Aspherical surface 2
K=-41.704463
A ₄ = 0.362699E+00
A ₆ = -0.534069E+00
A ₈ = 0.354745E+00
A ₁₀ = -0.793612E-01
A ₁₂ = -0.252257E-03

[0098] Incidentally, the diffraction surface can be expressed by the following expression as optical path difference function Φ_b , (which also applies to Example 26 explained later). In this case, h represents a height in the direction perpendicular to an optical axis, and b represents a coefficient of the optical path difference function.

$$\Phi_b = \sum_{i=1}^{\infty} b_{2i} h^{2i}$$

[0099] As stated above, in Examples 1 - 15, it was possible to obtain an aspherical single objective lens having a large numerical aperture and excellent image height characteristics as an objective lens for an optical pickup apparatus. For example, it was possible to obtain a single objective lens wherein the numerical aperture is 0.85 for wavelength of 400 nm, and rms of the wave front aberration is not more than 0.07λ (λ is a wavelength) for an image height at an angle of view of 1° , as shown in Example 1. Namely, it was possible to obtain an aspherical single objective lens for an optical pickup apparatus which has a large numerical aperture of 0.65 or more and excellent image height characteristics and is suitable for a high density recording and reproducing apparatus.

[0100] Further, in Examples 1 - 15, eccentricity sensitivity can be made excellent and spherical aberration and coma can be corrected satisfactorily.

[0101] Next, an example of a coupling lens will be explained. Table 24 below shows a list of data for Examples 16 - 27. Incidentally, objective lenses in Examples 16, 17, 20, 21 and 22 are the same as that in Example 8, objective lenses in Examples 18, 19, 23, 24, 25 and 26 are the same as that in Example 9, and an objective lens in Example 27 is the same as that in Example 13.

Table 24

Example	16	17	18	19	20	21
Material of an objective lens	Glass	Glass	Plastic	Plastic	Glass	Glass
Focal length of an objective lens	1.765	1.765	1.765	1.765	1.765	1.765
NA of an objective lens	0.85	0.85	0.85	0.85	0.85	0.85
Standard wave-length	405nm	405nm	405nm	405nm	405nm	405nm
Structure of a coupling lens	Spherical doublet	Spherical doublet	Spherical doublet	Spherical doublet	Aspherical doublet	Aspherical doublet
Divergent angle of a light flux emerging from a coupling lens	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux
$0.1 \leq m \leq 0.5$ ($m < 0$)	0.20	0.13	0.20	0.13	0.33	0.20
$\delta_{fb} \cdot NA^2 \leq 0.25 \mu m$ $0.02 \mu m \leq \delta_{fb} \cdot NA^2 \leq 0.15 \mu m$	0.14	0.087	0.16	0.12	0.071	0.034
(δ_{fb})	0.19	0.12	0.22	0.17	0.098	0.047

Table 24 (cont'd)

Example	22	23	24	25	26	27
Material of an objective lens	Glass	Plastic	Plastic	Plastic	Plastic	Glass having high refractive index
Focal length of an objective lens	1.765	1.765	1.765	1.765	1.765	1.765
NA of an objective lens	0.85	0.85	0.85	0.85	0.85	0.85
Standard wave-length	405nm	405nm	405nm	405nm	405nm	405nm
Structure of a coupling lens	Aspherical doublet	Aspherical doublet	Aspherical doublet	Aspherical doublet	Single diffraction lens	Aspherical doublet
Divergent angle of a light flux emerging from a coupling lens	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux	Collimated light flux
$0.1 \leq m \leq 0.5$ ($m < 0$)	0.13	0.33	0.20	0.13	0.29	0.10
$\delta_{fb} \cdot NA^2 \leq 0.25 \mu m$ $0.02 \mu m \leq \delta_{fb} \cdot NA^2 \leq 0.15 \mu m$	0.0031	0.10	0.060	0.031	0.12	0.06
(δ_{fb})	0.0043	0.14	0.083	0.043	0.17	0.08

(Example 16)

[0102] Lens data and an aspherical surface coefficient are shown in Table 25. Sectional views of a coupling lens of a one-group and two-element structure in Example 16 and an objective lens are shown in Fig. 25, and a diagram of spherical aberration is shown in Fig. 26.

Table 25

Surface No.		r (mm)	d (mm)	n	vd
Light source			6.410		
1	Coupling lens	-65.708	1.423	1.91409	23.8
2		5.042	2.242	1.75166	54.7
3		-5.033	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 1)	Objective lens	1.434	2.750	1.71558	53.2
5 (Aspherical surface 2)		-2.118	0.290		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2
K=-0.452646	K=-185.751580
A ₄ = 0.571669E-2	A ₄ = 0.281279
A ₆ = -0.591147E-2	A ₆ = -0.742134
A ₈ = 0.721339E-2	A ₈ = 0.667680
A ₁₀ = -0.398819E-2	A ₁₀ = -0.195290
A ₁₂ = 0.390519E-3	A ₁₂ = -0.252228E-3
A ₁₄ = 0.446956E-3	
A ₁₆ = -0.135385E-3	

(Example 17)

[0103] Lens data and an aspherical surface coefficient are shown in Table 26. Sectional views of a coupling lens of a one-group and two-element structure in Example 17 and an objective lens are shown in Fig. 27, and a diagram of spherical aberration is shown in Fig. 28.

Table 26

Surface No.		r (mm)	d (mm)	n	vd
Light source			9.838		
1	Coupling lens	-9.865	1.149	1.91409	23.8
2		5.102	2.500	1.75166	54.7
3		-4.713	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 1)	Objective lens	1.434	2.750	1.71558	53.2
5 (Aspherical surface 2)		-2.118	0.290		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2
K=-0.452646	K=-185.751580
A ₄ = 0.571669E-2	A ₄ = 0.281279
A ₆ = -0.591147E-2	A ₆ = -0.742134
A ₈ = 0.721339E-2	A ₈ = 0.667680
A ₁₀ = -0.398819E-2	A ₁₀ = -0.195290
A ₁₂ = 0.390519E-3	A ₁₂ = -0.252228E-3
A ₁₄ = 0.446956E-3	
A ₁₆ = -0.135385E-3	

(Example 18)

[0104] Lens data and an aspherical surface coefficient are shown in Table 27. Sectional views of a coupling lens of a one-group and two-element structure in Example 18 and an objective lens are shown in Fig. 29, and a diagram of spherical aberration is shown in Fig. 30.

Table 27

Surface No.		r (mm)	d (mm)	n	vd
Light source			6.410		
1	Coupling lens	-65.708	1.423	1.91409	23.8
2		5.042	2.242	1.75166	54.7
3		-5.033	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 1)	Objective lens	1.175	2.602	1.52523	59.5
5 (Aspherical surface 2)		-1.042	0.357		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2
K=-0.682004	K=-29.373780
A ₄ = 0.180213E-1	A ₄ = 0.297543
A ₆ = 0.368416E-2	A ₆ = -0.423018
A ₈ = 0.140365E-2	A ₈ = 0.295535
A ₁₀ = 0.342876E-3	A ₁₀ = -0.829290E-1
A ₁₂ = -0.311534E-4	A ₁₂ = -0.252257E-3
A ₁₄ = 0.103341E-3	
A ₁₆ = 0.141728E-4	

(Example 19)

[0105] Lens data and an aspherical surface coefficient are shown in Table 28. Sectional views of a coupling lens of a one-group and two-element structure in Example 19 and an objective lens are shown in Fig. 31, and a diagram of spherical aberration is shown in Fig. 32.

Table 28

Surface No.		r (mm)	d (mm)	n	vd
Light source			9.838		
1	Coupling lens	-9.865	1.149	1.91409	23.8
2		5.102	2.500	1.75166	54.7
3		-4.713	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 1)	Objective lens	1.175	2.602	1.52523	59.5
5 (Aspherical surface 2)		-1.042	0.357		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2
K=-0.682004	K=-29.373780
A ₄ = 0.180213E-1	A ₄ = 0.297543
A ₆ = 0.368416E-2	A ₆ = -0.423018
A ₈ = 0.140365E-2	A ₈ = 0.295535
A ₁₀ = 0.342876E-3	A ₁₀ = -0.829290E-1
A ₁₂ = -0.311534E-4	A ₁₂ = -0.252257E-3
A ₁₄ = 0.103341E-3	
A ₁₆ = 0.141728E-4	

(Example 20)

[0106] Lens data and an aspherical surface coefficient are shown in Table 29. Sectional views of a coupling lens of a one-group and two-element structure in Example 20 and an objective lens are shown in Fig. 33, and a diagram of spherical aberration is shown in Fig. 34.

Table 29

Surface No.		r (mm)	d (mm)	n	vd
Light source			3.342		
1	Coupling lens	9.926	1.600	1.91409	23.8
2		2.024	2.200	1.71548	53.2
3 (Aspherical surface 1)		-3.518	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.434	2.750	1.71558	53.2
5 (Aspherical surface 3)		-2.118	0.290		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.270078	K=0.452646	K=-185,751580
A ₄ = 0.425585E-3	A ₄ = 0.571669E-2	A ₄ = 0.281279
A ₆ = -0.968014E-3	A ₆ = -0.591147E-2	A ₆ = -0.742134
A ₈ = 0.315494E-3	A ₈ = 0.721339E-2	A ₈ = 0.667680
A ₁₀ = -0.970417E-4	A ₁₀ = -0.398819E-2	A ₁₀ = -0.195290
	A ₁₂ = 0.390519E-3	A ₁₂ = -0.252228E-3
	A ₁₄ = 0.446956E-3	
	A ₁₆ = -0.135385E-3	

(Example 21)

[0107] Lens data and an aspherical surface coefficient are shown in Table 30. Sectional views of a coupling lens of a one-group and two-element structure in Example 16 and an objective lens are shown in Fig. 35, and a diagram of spherical aberration is shown in Fig. 36.

Table 30

Surface No.		r(mm)	d(mm)	n	vd
Light source			7.230		
1	Coupling lens	13.531	1.000	1.91409	23.8
2		2.551	2.100	1.71548	53.2
3 (Aspherical surface 1)		-5.765	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.434	2.750	1.71558	53.2
5 (Aspherical surface 3)		-2.118	0.290		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.699858	K=-0.452646	K=-185.751580
A ₄ = -0.53797E-3	A ₄ = 0.571669E-2	A ₄ = 0.281279
A ₆ = -0.352488E-3	A ₆ = -0.591147E-2	A ₆ = -0.742134
A ₈ = 0.595790E-4	A ₈ = 0.721339E-2	A ₈ = 0.667680
A ₁₀ = -0.152115E-4	A ₁₀ = -0.398819E-2	A ₁₀ = -0.195290
	A ₁₂ = 0.390519E-3	A ₁₂ = -0.25228E-3
	A ₁₄ = 0.446956E-3	
	A ₁₆ = -0.135385E-3	

(Example 22)

[0108] Lens data and an aspherical surface coefficient are shown in Table 31. Sectional views of a coupling lens of a one-group and two-element structure in Example 22 and an objective lens are shown in Fig. 37, and a diagram of spherical aberration is shown in Fig. 38.

Table 31

Surface No.		r (mm)	d (mm)	n	vd
Light source			11.961		
1	Coupling lens	37.967	0.900	1.91409	23.8
2		2.857	2.000	1.71548	53.2
3 (Aspherical surface 1)		-6.448	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.434	2.750	1.71558	53.2
5 (Aspherical surface 3)		-2.118	0.290		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.980965	K=-0.452646	K=-185.751580
A ₄ = -0.719068E-3	A ₄ = 0.571669E-2	A ₄ = 0.281279
A ₆ = -0.177543E-3	A ₆ = -0.591147E-2	A ₆ = -0.742134
A ₈ = 0.364218E-4	A ₈ = 0.721339E-2	A ₈ = 0.667680
A ₁₀ = -0.120077E-4	A ₁₀ = -0.398819E-2	A ₁₀ = -0.195290
	A ₁₂ = 0.390519E-3	A ₁₂ = -0.25228E-3
	A ₁₄ = 0.446956E-3	
	A ₁₆ = -0.135385E-3	

(Example 23)

[0109] Lens data and an aspherical surface coefficient are shown in Table 32. Sectional views of a coupling lens of a one-group and two-element structure in Example 23 and an objective lens are shown in Fig. 39, and a diagram of spherical aberration is shown in Fig. 40.

Table 32

Surface No.		r (mm)	d (mm)	n	vd
Light source			3.342		
1	Coupling lens	9.926	1.600	1.91409	23.8
2		2.024	2.200	1.71548	53.2
3 (Aspherical surface 1)		-3.518	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.175	2.602	1.5253	59.5
5 (Aspherical surface 3)		-1.042	0.357		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.270078	K=-0.682004	K=-29.373780
A ₄ = 0.425585E-3	A ₄ = 0.180213E-1	A ₄ = 0.297543
A ₆ = -0.968014E-3	A ₆ = 0.368416E-2	A ₆ = -0.423018
A ₈ = 0.315494E-3	A ₈ = 0.140365E-2	A ₈ = 0.295535
A ₁₀ = -0.970417E-4	A ₁₀ = 0.342876E-3	A ₁₀ = -0.829290E-1
	A ₁₂ = -0.311534E-4	A ₁₂ = -0.252257E-3
	A ₁₄ = 0.103341E-3	
	A ₁₆ = 0.141728E-4	

(Example 24)

[0110] Lens data and an aspherical surface coefficient are shown in Table 33. Sectional views of a coupling lens of a one-group and two-element structure in Example 24 and an objective lens are shown in Fig. 41, and a diagram of spherical aberration is shown in Fig. 42.

Table 33

Surface No.		r (mm)	d (mm)	n	vd
Light source			7.230		
1	Coupling lens	13.531	1.000	1.91409	23.8
2		2.551	2.100	1.71548	53.2
3 (Aspherical surface 1)		-5.765	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.175	2.602	1.52523	59.5
5 (Aspherical surface 3)		-1.042	0.357		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.699858	K=-0.682004	K=-29.373780
A ₄ = -0.53797E-3	A ₄ = 0.180213E-1	A ₄ = 0.297543
A ₆ = -0.352488E-3	A ₆ = 0.368416E-2	A ₆ = -0.423018
A ₈ = 0.595790E-4	A ₈ = 0.140365E-2	A ₈ = 0.295535
A ₁₀ = -0.152115E-4	A ₁₀ = 0.342876E-3	A ₁₀ = -0.829290E-1
	A ₁₂ = -0.311534E-4	A ₁₂ = -0.252257E-3
	A ₁₄ = 0.103341E-3	
	A ₁₆ = 0.141728E-4	

(Example 25)

[0111] Lens data and an aspherical surface coefficient are shown in Table 34. Sectional views of a coupling lens of a one-group and two-element structure in Example 25 and an objective lens are shown in Fig. 43, and a diagram of spherical aberration is shown in Fig. 44.

Table 34

Surface No.		r (mm)	d (mm)	n	vd
Light source			11.961		
1	Coupling lens	37.967	0.900	1.91409	23.8
2		2.857	2.000	1.71548	53.2
3 (Aspherical surface 1)		-6.448	5.000		
Diaphragm		∞	0		
4 (Aspherical surface 2)	Objective lens	1.175	2.602	1.52523	59.5
5 (Aspherical surface 3)		-1.042	0.357		
6	Transparent base plate	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.980965	K=-0.682004	K=-29.373780
A ₄ = -0.719068E-3	A ₄ = 0.180213E-1	A ₄ = 0.297543
A ₆ = -0.177543E-3	A ₆ = 0.368416E-2	A ₆ = -0.423018
A ₈ = 0.364218E-4	A ₈ = 0.140365E-2	A ₈ = 0.295535
A ₁₀ = -0.120077E-4	A ₁₀ = 0.342876E-3	A ₁₀ = -0.829290E-1
	A ₁₂ = -0.311534E-4	A ₁₂ = -0.252257E-3
	A ₁₄ = 0.103341E-3	
	A ₁₆ = 0.141728E-4	

(Example 26)

[0112] Lens data and an aspherical surface coefficient are shown in Table 35. Sectional views of a coupling lens of a one-group and two-element structure in Example 26 and an objective lens are shown in Fig. 45, and a diagram of spherical aberration is shown in Fig. 46.

Table 35

Surface No.		r (mm)	d (mm)	n	vd
Light source			5.103		
1 (Aspherical surface 1)	Coupling lens	15.399	2.000	1.52523	59.5
2 (Aspherical surface 2, Diffraction surface)		-5.37697	5		
Diaphragm			0		
3 (Aspherical surface 3)	Objective lens	1.175	2.602	1.52523	59.5
4 (Aspherical surface 4)		-1.042	0.357		
5	Transparent base plate	∞	0.1	1.61950	30.0
6		∞			
Image plane					

Aspherical surface 1	Aspherical surface 2	Diffraction surface
K= 0 A ₄ = -0.418319E-1 A ₆ = 0.416634E-1 A ₈ = -0.159039E-1 A ₁₀ = 0.134507E-2	K= 0 A ₄ = -0.22293E-2 A ₆ = -0.44722E-3 A ₈ = 0.25384E-2 A ₁₀ = -0.46638E-3	b ₂ = -0.18000E-1 b ₄ = -0.80593E-2 b ₆ = 0.62172E-2 b ₈ = -0.26442E-2 b ₁₀ = 0.35943E-3

Aspherical surface 3	Aspherical surface 4
K=-0.682004 A ₄ = 0.180213E-1 A ₆ = 0.368416E-2 A ₈ = 0.140365E-2 A ₁₀ = 0.342876E-3 A ₁₂ = -0.311534E-4 A ₁₄ = 0.103341E-3 A ₁₆ = 0.141728E-4	K=-29.373780 A ₄ = 0.297543 A ₆ = -0.423018 A ₈ = 0.295535 A ₁₀ = -0.829290E-1 A ₁₂ = -0.252257E-3

(Example 27)

[0113] Lens data and an aspherical surface coefficient are shown in Table 36. Sectional views of a coupling lens of a one-group and two-element structure in Example 27 and an objective lens are shown in Fig. 47, and a diagram of spherical aberration is shown in Fig. 48.

Table 36

Surface No.		r (mm)	d (mm)	n	vd
Light source			9.531		
1	Coupling lens	-11.04660	0.800	2.34749	16.6
2		1.55601	2.000	1.71548	53.3
3 (Aspherical surface 1)		-1.99414	5.000		
Diaphragm			0		
4 (Aspherical surface 2)	Objective lens	2.3000	3.650	2.15857	21.1
5 (Aspherical surface 3)		-2.73024	0.200		
6	Transparent base plate	∞	0.1	1.61950	30.0
7		∞			
Image plane					

Aspherical surface 1	Aspherical surface 2	Aspherical surface 3
K= 0.53298	K=-0.456357	K= 219.931
A ₄ = 0.342156E-2	A ₄ = 0.712833E-3	A ₄ = -0.962060E-1
A ₆ = 0.133722E-2	A ₆ = -0.604365E-3	A ₆ = -0.200434
A ₈ = -0.414740E-3	A ₈ = 0.898662E-3	A ₈ = 0.741851
A ₁₀ = 0.257160E-3	A ₁₀ = -0.133726E-2	A ₁₀ = -0.292121
	A ₁₂ = 0.785181E-3	A ₁₂ = -0.252226E-3
	A ₁₄ = -0.223083E-3	
	A ₁₆ = 0.199958E-4	

[0114] Since the objective lens of the invention is a single objective lens of a refraction system as stated above, there is caused axial chromatic aberration which is under on the part of a short wavelength. However, it was possible, in Examples 16 - 27, to correct the axial chromatic aberration by a coupling lens in the composition system of an objective lens and a coupling lens. It was possible to reduce the axial chromatic aberration of the objective lens by making the axial chromatic aberration of the coupling lens to be over on the part of the short wavelength.

[0115] Further, in Examples 16 - 27, image height characteristics are also excellent. In addition, eccentricity sensitivity can be made excellent and spherical aberration and coma can be corrected satisfactorily.

(Example 28)

[0116] Another example of the objective lens will be shown next. Lens data and aspherical surface coefficients are shown in Table 37. A sectional view of the objective lens in Example 28 is shown in Fig. 49 and an aberration diagram is shown in Fig. 50.

Table 37

$\gamma=405$ (nm) $f=1.765$ (mm) $NA=0.85$ Magnification = 0				
	r(mm)	d(mm)	N	vd
1*	1.19392	2.650	1.52491	56.5
2*	-0.97515	0.355		
3	∞	0.100	1.61950	30.0
4	∞	0.000		

* Aspherical surface

Aspherical surface coefficient

First surface

[0117]

K=-0.683354
A 4= 0.162029E-01
A 6= 0.154908E-02
A 8= 0.289288E-02
A10=-0.367711E-03
A12=-0.358222E-03
A14= 0.148419E-03
A16= 0.119603E-03
A18=-0.302302E-04
A20=-0.110520E-04

Second Surface

[0118]

K=-21.704418
A 4= 0.308021E+00
A 6=-0.639499E+00
A 8= 0.585364E+00
A10=-0.215623E+00
A12=-0.252265E-03

[0119] Table 38 shows various values.

Table 38

Example	28
f	1.76
NA	0.85
Wavelength (nm)	405
d1/f	1.50
f/vd	0.031

EP 1 081 692 A2

Table 38 (continued)

Example		28
vd		56.5
r1(n · f)		0.44
n		1.52491
Wave front aberration	Axial	0.006
	Off-axis	0.086
	(Image height)	(0.03mm)
	(Angle of view)	(1°)

[0120] In Example 28, since wave front aberration caused by the first surface that is decentered by 1 μm is 0.026 λ (it is preferable to be 0.035 λ or less), eccentricity sensitivity is corrected to be excellent.

[0121] In the following Examples 29 - 32, there are shown examples wherein spherical aberrations fluctuate. Optical pickup apparatus used in Examples 29 - 32 has uniaxial actuator 11 which is shown in Fig. 57 and shifts a coupling lens in the optical axis direction. An objective lens in each of Examples 29 - 32 is the same as that in Example 28.

(Example 29)

[0122] Lens data and aspherical surface coefficients are shown in Table 39. A sectional view of the optical system is shown in Fig. 51 and an aberration diagram is shown in Fig. 52.

Table 39

Surface No.		r(mm)	d(mm)	n	vd
Light source			d0 (variable)		
1	Coupling lens	-62.022	1.200	1.52491	56.5
2		-4.608	d2 (variable)		
Diaphragm		∞	0		
3 (Aspherical surface 2)	Objective lens	1.194	2.650	1.52491	56.5
4 (Aspherical surface 3)		-0.975	0.355		
5	Transparent base board	∞	0.100	1.61950	30.0
6		∞			

Aspherical surface 1

[0123]

K=-2.4335E-01
A 4= 2.7143E-03
A 6=-5.6745E-05
A 8= 7.0168E-05
A10=-1.5659E-05

Diffraction surface 1

[0124]

b2= 2.0000E-02
b4=-1.3821E-03

Aspherical surface 2

[0125]

5 K=-0.683354
A 4= 0.162029E-01
A 6= 0.154908E-02
A 8= 0.289288E-02
A10=-0.367711E-03
10 A12=-0.358222E-03
A14= 0.148419E-03
A16= 0.119603E-03
A18=-0.302302E-04
A20=-0.110520E-04

Aspherical surface 3

[0126]

20 K=-21.704418
A 4= 0.308021E+00
A 6=-0.639499E+00
A 8= 0.585364E+00
A10=-0.215623E+00
25 A12=-0.252265E-03

[0127]

Table 40

Causes of fluctuation of spherical aberration		WFE-rms after correction	d0(mm)	d2(mm)
Standard conditions ($\lambda_c=405\text{nm}$, $T_c=25^\circ\text{C}$, $t_c=0.1\text{mm}$)		0.007λ	6.000	5.000
Wavelength fluctuation of LD	$\Delta\lambda=+10\text{nm}$	0.008λ	5.941	5.059
	$\Delta\lambda=-10\text{nm}$	0.022λ	6.054	4.946
Temperature change	$\Delta T=+30^\circ\text{C}$	0.011λ	5.927	5.073
	$\Delta T=-30^\circ\text{C}$	0.031λ	6.071	4.929
Error of transparent base board thickness	$\Delta t=+0.02\text{mm}$	0.004λ	5.853	5.147
	$\Delta t=-0.02\text{mm}$	0.015λ	6.152	4.848

[0128] In the present example, an objective lens and a coupling lens are made to be a plastic lens. Further, the coupling lens is made to be a single diffraction lens, and axial chromatic aberration is corrected excellently by the simple structure.

[0129] Table 40 shows that spherical aberration caused by wavelength fluctuation of a laser, temperature change and by errors in thickness of transparent base board is corrected excellently.

(Example 30)

[0130] Lens data and aspherical surface coefficients are shown in Table 41. A sectional view of the optical system is shown in Fig. 53 and an aberration diagram is shown in Fig. 54.

EP 1 081 692 A2

Table 41

Surface No.		r(mm)	d(mm)	n	vd
Light source			d0 (variable)		
1 (Aspherical surface 1, diffraction surface 1)	Coupling lens	-226.959	1.200	1.52491	56.5
2 (Aspherical surface 2, diffraction surface 2)		-6.733	d2 (variable)		
Diaphragm		∞	0		
3 (Aspherical surface 3)	Objective lens	1.194	2.650	1.52491	56.5
4 (Aspherical surface 4)		-0.975	0.355		
5	Transparent base board	∞	0.100	1.61950	30.0
6		∞			

EP 1 081 692 A2

5

10

15

20

25

30

35

40

45

50

Aspherical surface 1	Diffraction surface 1
K=0.0 A4=1.0245E-02 A6=9.6650E-04 A8=-5.9104E-04 A10=8.9735E-05	b2=-2.2967E-02 b4=2.1037E-03
Aspherical surface 2	Diffraction surface 2
K=-4.3181 A4=1.5848E-03 A6=8.6137E-04 A8=-2.0117E-04 A10=1.3168E-05	b2=-1.7113E-02 b4=8.2815E-04
Aspherical surface 3	
K=-0.683354 A4=0.162029E-01 A6=0.154908E-02 A8=0.289288E-02 A10=-0.367711E-03 A12=-0.358222E-03 A14=0.148419E-03 A16=0.119603E-03 A18=-0.302302E-04 A20=-0.110520E-04	
Aspherical surface 4	
K=-21.704418 A4=0.308021E+00 A6=-0.639499E+00 A8=0.585364E+00 A10=-0.215623E+00 A12=-0.252265E-03	

Table 42

55

Causes of fluctuation of spherical aberration	WFE-rms after correction	d0(mm)	d2(mm)
Standard conditions ($\lambda_c=405\text{nm}$, $T_c=25^\circ\text{C}$, $t_c=0.1\text{mm}$)	0.008 λ	6.000	5.000

EP 1 081 692 A2

Table 42 (continued)

Causes of fluctuation of spherical aberration		WFE-rms after correction	d0(mm)	d2(mm)
Wavelength fluctuation of LD	$\Delta\lambda=+10\text{nm}$	0.009λ	5.869	5.131
	$\Delta\lambda=-10\text{nm}$	0.010λ	6.141	4.859
Temperature change	$\Delta T=+30^\circ\text{C}$	0.006λ	5.905	5.095
	$\Delta T=-30^\circ\text{C}$	0.025λ	6.101	4.899
Error of transparent base board thickness	$\Delta t=+0.02\text{mm}$	0.003λ	5.867	5.133
	$\Delta t=-0.02\text{mm}$	0.014λ	6.139	4.861

[0131] In the present example, an objective lens and a coupling lens are made to be a plastic lens. Further, the coupling lens is made to be a single both-sided diffraction lens, and deterioration of wave front aberration caused by mode hop is prevented.

[0132] Table 42 shows that spherical aberration caused by wavelength fluctuation of a laser, temperature change and by errors in thickness of transparent base board is corrected excellently.

(Example 31)

[0133] Lens data and aspherical surface coefficients are shown in Table 43. A sectional view of the optical system is shown in Fig. 55 and an aberration diagram is shown in Fig. 56.

Table 43

Surface No.		r(mm)	d(mm)	n	vd
Light source			d0 (variable)		
1	Coupling lens	13.531	1.000	1.91409	23.8
2		2.551	2.100	1.71548	53.2
3 (Aspherical surface 1)		-5.765	d3 (variable)		
Diaphragm		∞	0		
3 (Aspherical surface 2)	Objective lens	1.194	2.650	1.52491	56.5
4 (Aspherical surface 3)		-0.975	0.355		
6	Transparent base board	∞	0.100	1.61950	30.0
7		∞			

Aspherical surface 1

[0134]

K=0.699858
A4=-0.53797E-3
A6=-0.352488E-3
A8=0.595790E-4
A10=-0.152115E-4

Aspherical surface 2

[0135]

K=-0.683354

A4=0.162029E-01
 A6=0.154908E-02
 A8=0.289288E-02
 A10=-0.367711E-03
 A12=-0.358222E-03
 A14=0.148419E-03
 A16=0.119603E-03
 A18=-0.302302E-04
 A20=-0.110520E-04

Aspherical surface 3

[0136]

K=-21.704418
 A4=0.308021E+00
 A6=-0.639499E+00
 A8=0.585364E+00
 A10=-0.215623E+00
 A12=-0.252265E-03

Table 44

Causes of fluctuation of spherical aberration		WFE-rms after correction	d0 (mm)	d3 (mm)
Standard conditions ($\lambda_c=405\text{nm}$, $T_c=25^\circ\text{C}$, $t_c=0.1\text{mm}$)		0.008 λ	7.230	5.000
Wavelength fluctuation of LD	$\Delta\lambda=+10\text{nm}$	0.008 λ	7.134	5.096
	$\Delta\lambda=-10\text{nm}$	0.019 λ	7.330	4.900
Temperature change	$\Delta T=+30^\circ\text{C}$	0.015 λ	7.050	5.180
	$\Delta T=-30^\circ\text{C}$	0.027 λ	7.415	4.815
Error of transparent base board thickness	$\Delta t=+0.02\text{mm}$	0.006 λ	6.987	5.243
	$\Delta t=-0.02\text{mm}$	0.015 λ	7.486	4.744

[0137] A plastic lens is used as an objective lens. A coupling lens is made to be a doublet lens of a one-group and two-element type. Further, the surface of the lens closer to an optical information recording medium is made to be an aspherical surface. Due to this, compactness and high NA are attained.

[0138] Table 44 shows that spherical aberration caused by wavelength fluctuation of a laser, temperature change and by errors in thickness of transparent base board is corrected excellently.

[0139] Various parameters in Examples 27 - 31 are shown in Table 45.

Table 45

Example	29	30	31
Material of objective lens	Plastic	Plastic	Plastic
Focal length of objective lens	1.765	1.765	1.765
NA of objective lens	0.85	0.85	0.85
Standard wavelength	405nm	405nm	405nm
Structure of coupling lens	Single diffraction lens	Single diffraction lens	Aspherical surface doulet
Divergent angle of light flux emitted from coupling lens	Collimated light flux	Collimated light flux	Collimated light flux

EP 1 081 692 A2

Table 45 (continued)

Example	29	30	31
$0.1 \leq m \leq 0.5$ ($m < 0$)	0.26	0.27	0.2
$\delta f_B \cdot NA^2 \leq 0.25 \mu m$ $0.02 \mu m \leq \delta f_B \cdot NA^2 \leq 0.15 \mu m$	0.061	-0.061	0.032
(δf_B)	0.084	-0.085	0.044

(Example 32)

[0140] The example wherein a diffraction surface is provided only on one side of a single coupling lens will be shown, next. Lens data and aspherical surface coefficients are shown in Table 46.

Table 46

Surface No.		r(mm)	d(mm)	n	vd
Light source			d0 (variable)		
1 (Diffraction surface 1)	Coupling lens	∞	1.200	1.52491	56.5
2 (Aspherical surface 1)		-16.084	d2 (variable)		
Diaphragm		∞	0		
3 (Aspherical surface 2)	Objective lens	1.194	2.650	1.52491	56.5
4 (Aspherical surface 3)		-0.975	0.355		
5	Transparent base board	∞	0.100	1.61950	30.0
6		∞			

Diffraction surface 1

[0141]

b2=-2.6023E-02
b4=-2.1722E-04

Aspherical surface 1

K=17.997115
A4=0.759036E-03
A6=0.311883E-03
A8=-0.123894E-03
A10=0.196179E-04

Aspherical surface 2

[0142]

K=-0.683354
A4=0.162029E-01
A6=0.154908E-02
A8=0.289288E-02
A10=-0.367711E-03
A12=-0.358222E-03
A14=0.148419E-03
A16=0.119603E-03
A18=-0.302302E-04

A20=-0.110520E-04

Aspherical surface 3

[0143]

K=-21.704418
 A4=0.308021E+00
 A6=-0.639499E+00
 A8=0.585364E+00
 A10=-0.215623E+00
 A12=-0.252265E-03

Table 47

Causes of fluctuation of spherical aberration		WFE-rms after correction	d0 (mm)	d2 (mm)
Standard conditions ($\lambda_c=405\text{nm}$, $T_c=25^\circ\text{C}$, $t_c=0.1\text{mm}$)		0.005λ	11.670	5.000
Wavelength fluctuation of LD	$\Delta\lambda=+10\text{nm}$	0.008λ	11.404	5.266
	$\Delta\lambda=-10\text{nm}$	0.009λ	11.960	4.710
Temperature change	$\Delta T=+30^\circ\text{C}$	0.014λ	11.373	5.297
	$\Delta T=-30^\circ\text{C}$	0.018λ	11.995	4.676
Error of transparent base board thickness	$\Delta t=+0.02\text{mm}$	0.009λ	11.246	5.424
	$\Delta t=-0.02\text{mm}$	0.008λ	12.136	4.534

[0144] In the present example, a plastic lens is used for an objective lens and for a coupling lens. Fluctuations of optimum recording position caused by wavelength shift can be controlled to be small, and deterioration of wave front aberration caused by mode hop is prevented. In addition, deterioration of wave front aberration caused by surface eccentricity of the coupling lens is prevented by providing the diffraction surface only on one side of the coupling lens. Further, by providing the diffraction surface on the surface of the coupling lens closer to the light source and by providing on the surface of the coupling lens closer to the objective lens the aspherical surface on which the refracting power generated at a location is weaker when the location is farther from the optical axis, wave front aberration caused by eccentricity of the coupling lens and by tracking error is prevented. Table 47 shows that spherical aberration caused by wavelength fluctuation of a laser, temperature change and by errors in thickness of transparent base board can be corrected excellently. Axial chromatic aberration can also be corrected excellently. Various parameters in Examples 32 are shown in Table 48.

Table 48

Example	32
Material of objective lens	Plastic
Focal length of objective lens	1.765
NA of objective lens	0.85
Standard wavelength	405nm
Structure of coupling lens	Single diffraction lens
Divergent angle of light flux emitted from coupling lens	Collimated light flux
$0.1 \leq m \leq 0.5$ ($m < 0$)	0.15
$\delta f_B \cdot \text{NA}^2 \leq 0.25\mu\text{m}$ $0.02\mu\text{m} \leq \delta f_B \cdot \text{NA}^2 \leq 0.15\mu\text{m}$	0.05

Table 48 (continued)

Example	32
(δf_B)	-0.069

[0145] The invention makes it possible to provide an aspherical single objective lens having a large numerical aperture and excellent image height characteristics, so that it may be used as an objective lens of an optical pickup apparatus. In particular, it is possible to provide an objective lens which has a large numerical aperture of 0.75 or more and is suitably used for a high density recording and reproducing apparatus employing a laser wherein a wavelength of a light source is as short as about 400 nm.

[0146] Further, eccentricity sensitivity can be made excellent and spherical aberration and coma can be corrected satisfactorily.

[0147] It is also possible to provide an objective lens suitably used for a recording and reproducing apparatus which can operate under conditions that a thickness of a protective layer of an information recording medium is as thin as about 0.1 mm and a working distance is short.

[0148] It is further possible to provide an optical pickup apparatus which employs the objective lens stated above.

[0149] Further, in a high density and optical recording and reproducing apparatus, it is possible to provide an optical pickup apparatus having an optical system wherein axial chromatic aberration has been corrected by simple structures. In particular, it is possible to provide an optical pickup apparatus wherein a numerical aperture on the part of an information recording medium is as large as 0.65 or more, and the shortest wavelength of a light source to be used is as small as 500 nm or less.

[0150] Disclosed embodiment can be varied by a skilled person without departing from the spirit and scope of the invention.

Claims

1. An objective lens for use in an optical pickup apparatus to record or reproduce information in an optical information recording medium, comprising:

an aspheric surface;
wherein the following conditional formula is satisfied:

$$1.1 \leq d_1/f \leq 3$$

where d_1 represents axial lens thickness and f represents a focal length.

2. The objective lens of claim 1, wherein a numerical aperture of the objective lens is not smaller than 0.65.
3. The objective lens of claim 2, wherein a numerical aperture of the objective lens is not smaller than 0.75.
4. The objective lens of claim 1, wherein the following conditional formula is satisfied:

$$f/v_d \leq 0.060$$

where v_d represents Abbe's number.

5. The objective lens of claim 1, wherein the following conditional formula is satisfied:

$$1.40 \leq n$$

where n represents a refractive index at a used wavelength.

6. The objective lens of claim 5, wherein the following conditional formula is satisfied:

$$1.40 \leq n \leq 1.85$$

7. The objective lens of claim 1, wherein the following conditional formula is satisfied:

EP 1 081 692 A2

$$0.40 \leq r1/(n \cdot f) \leq 0.70$$

where r1 represents a paraxial radius of curvature of one surface of the objective lens.

5 8. The objective lens of claim 7, wherein r1 represents a paraxial radius of curvature of the surface of the objective lens at the light source side.

9. The objective lens of claim 1, wherein a used wavelength is not longer than 500 nm.

10 10. The objective lens of claim 1, wherein the objective lens is an objective lens for use in an optical pickup apparatus to record or reproduce information in an optical information recording medium having a protective layer whose thickness is not larger than 0.2 mm.

11. The objective lens of claim 10, wherein a numerical aperture is not smaller than 0.7.

15

12. The objective lens of claim 7, wherein the following conditional formula is satisfied:

$$1.50 \leq n$$

20

where n represents a refractive index at a used wavelength.

13. The objective lens of claim 1, wherein the objective lens is a plastic lens.

14. The objective lens of claim 1, wherein the objective lens is a glass lens.

25

15. The objective lens of claim 1, wherein the following conditional formula is satisfied:

$$1.85 \leq n$$

30

where n represents a refractive index at a used wavelength.

16. The objective lens of claim 1, further comprising a diffracting section.

17. The objective lens of claim 1, further comprising a flange section on an outer periphery thereof.

35

18. The objective lens of claim 17, wherein the flange section comprises a surface extended in a direction perpendicular to an optical axis.

19. The objective lens of claim 1, wherein each of both lens surfaces is an aspherical surface.

40

20. An optical pickup apparatus to record or reproduce information in an optical information recording medium, comprising:

a light source to emit light flux;

45

a converging optical system to condense the light flux emitted from the light source; and

an optical detector to detect reflection light from the optical information recording medium;

wherein the converging optical system comprises an objective lens to condense the light flux on an information recording surface of the optical information recording medium and the objective lens comprises an aspheric surface; and wherein the following conditional formula is satisfied:

50

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective lens.

55

21. The optical pickup apparatus of claim 20, wherein a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.65.

EP 1 081 692 A2

22. The optical pickup apparatus of claim 20, wherein a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.75.

23. The optical pickup apparatus of claim 20, wherein the following conditional formula is satisfied:

$$f/vd \leq 0.060$$

where vd represents Abbe's number of the material of the objective lens.

24. The optical pickup apparatus of claim 20, wherein the following conditional formula is satisfied:

$$1.40 \leq n$$

where n represents a refractive index of the material of the objective lens at a used wavelength.

25. The optical pickup apparatus of claim 24, wherein the following conditional formula is satisfied:

$$1.40 \leq n \leq 1.85$$

26. The optical pickup apparatus of claim 20, wherein the following conditional formula is satisfied:

$$0.40 \leq r1/(n \cdot f) \leq 0.70$$

where r1 represents a paraxial radius of curvature of the surface of the objective lens at the light source side.

27. The optical pickup apparatus of claim 20, wherein the light source emits light flux whose wavelength is not larger than 500 nm.

28. The optical pickup apparatus of claim 20, wherein the optical pickup apparatus is used to record or reproduce information in an optical information recording medium having a protective layer whose thickness is not larger than 0.2 mm.

29. The optical pickup apparatus of claim 28, wherein a numerical aperture of the objective lens at the optical information recording medium side is not smaller than 0.7.

30. The optical pickup apparatus of claim 20, wherein the following conditional formula is satisfied:

$$1.85 \leq n$$

where n represents a refractive index of a material of the objective lens at a wavelength of the light flux emitted from the light source.

31. The optical pickup apparatus of claim 20, wherein the converging optical system comprises a diffracting section.

32. The optical pickup apparatus of claim 20, wherein the converging optical system comprises a coupling lens to change a divergent angle of the light flux emitted from the light source and the coupling lens corrects chromatic aberration of the objective lens.

33. The optical pickup apparatus of claim 32, wherein the coupling lens is a collimator lens to make the light flux emitted from the light source to be parallel light flux.

34. The optical pickup apparatus of claim 32, wherein chromatic aberration of the composite system of the objective lens and the coupling lens satisfies the following conditional formula:

$$\delta fb \cdot NA^2 \leq 0.25 \mu m (\delta fb > 0)$$

where δfb represents a change of focal position(μm) of the composite system when a wavelength is changed from a standard wavelength by +1 nm, and NA represents a numerical aperture of the objective lens at the optical infor-

mation recording medium side.

35. The optical pickup apparatus of claim 34, wherein the chromatic aberration of the composite system of the objective lens and the coupling lens satisfies the following conditional formula:

$$0.02 \mu\text{m} \leq \delta f_b \cdot \text{NA}^2 \leq 0.15 \mu\text{m} (\delta f_b > 0)$$

36. The optical pickup apparatus of claim 32, wherein the following conditional formula is satisfied:

$$0.1 \leq |m| \leq 0.5 (m < 0)$$

where m represents magnification of the composite system of the objective lens and the coupling lens.

37. The optical pickup apparatus of claim 32, wherein the coupling lens is a single lens group having two lenses.

38. The optical pickup apparatus of claim 32, wherein the coupling lens comprises an aspherical surface.

39. The optical pickup apparatus of claim 32, wherein the coupling lens comprises a diffracting section.

40. An apparatus to record or reproduce information in an optical information recording medium, comprising:

an optical pickup apparatus, comprising

a light source to emit light flux;

a converging optical system to condense the light flux emitted from the light source; and

an optical detector to detect reflection light or transmission light from the optical information recording medium;

wherein the converging optical system comprises an objective lens to condense the light flux on an information recording surface of the optical information recording medium and the objective lens comprises an aspheric surface; and wherein the following conditional formula is satisfied:

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective lens.

41. A method of recording or reproducing information in an optical information recording medium, comprising:

a step of emitting light flux;

a step of converging the light flux emitted from the light source on an information recording surface of the optical information recording medium; and

a step of detecting reflection light or transmission light of the light condensed on the information recording surface;

wherein the light flux is converged on the information recording surface of the optical information recording medium by an objective lens; and

wherein the objective lens comprises an aspheric surface and the following conditional formula is satisfied:

$$1.1 \leq d1/f \leq 3$$

where d1 represents axial lens thickness of the objective lens and f represents a focal length of the objective lens.

FIG. 1 (a)




FIG. 1 (b)




FIG. 2 (a)




FIG. 2 (b)




FIG. 3 (a)




FIG. 3 (b)




FIG. 4 (a)




FIG. 4 (b)




FIG. 5 (a)




FIG. 5 (b)




FIG. 6 (a)




FIG. 6 (b)




FIG. 7 (a)




FIG. 7 (b)




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57

